



RADIAL OTR TYRES

Tyre Size	Ply Rating	Compound Code	Load Index	Speed Symbol	Type	Pattern	Overall Width (mm)	Overall Width (in.)	Overall Diameter (mm)	Overall Diameter (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Standard Rim	Tyre Valve	Tread Depth (mm)	Tread Depth (32nds)
HIGHWAY APPLICATION																		
385/95R24	☆☆☆	—	170	E	TT	GL904 (E-2)	385	15.2	1365	53.7	900	131	6000	13200	10.00W	TL	20.5	25.8
385/95R25	☆☆☆	—	170	E	TL	GL904(E-2)	385	15.2	1365	53.7	900	131	6000	13200	10.00/1.5	TL	20.5	25.8
445/95R25	☆☆	—	177	E	TL	GL905	436	17.2	1480	58.3	900	131	7300	16100	11.25/2.0	TL	25.5	32.1
GRADER																		
17.5R25	☆	1S	153	A8	TL	GL903 (G-2)	445	17.5	1360	53.5	300	44	3650	8050	14.00/1.5	TL	27.5	34.6
17.5R25	☆	2S	153	A8	TL	GL903 (G-2)	445	17.5	1360	53.5	300	44	3650	8050	14.00/1.5	TL	27.5	34.6
13.00R24	☆	1S	146	A8	TL	GL982 (G-2)	330	13.0	1296	51.0	375	54	3000	6600	8.00TG	TL	30.0	37.8
14.00R24	TG☆	—	153	A8	TL	GL982 (G-2)	360	14.2	1360	53.5	375	54	3650	8050	8.00TG	TL	28.5	35.9
14.00R24	☆	—	165	A8	TL	GL982 (G-2)	376	14.8	1360	53.5	625	91	5150	11400	10.00VA	TL	28.5	35.9
LOADERS																		
17.5R25	☆	2S	176	A2	TL	GL903 (L-2)	445	17.5	1360	53.5	500	73	7100	15700	14.00/1.5	TL	27.5	34.6
20.5R25	☆	2S	186	A2	TL	GL902 (L-3)	532	20.9	1482	58.3	500	73	9500	20900	17.00/2.0	TL	33.0	41.6
23.5R25	☆☆	2S	195	A2	TL	GL902 (L-3)	617	24.3	1637	64.4	500	73	12100	26700	19.50/2.5	TL	40	50.4
23.5R25	☆	2S	195	A2	TT	GL902 (L-3)	617	24.3	1637	64.4	500	73	12100	26700	19.50/2.5	TT	40	50.4
26.5R25	☆	2S	202	A2	TL	GL902 (L-3)	675	26.6	1755	69.1	500	73	15000	33100	22.00/3.0	TL	45.5	57.3
29.5R25	☆	2S	208	A2	TL	GL902(L-3)	770	30.3	1880	74.0	500	73	18000	38700	25.00/3.5	TL	50.0	63.0
26.5R25	☆	3S	202	A2	TL	GL902 (L-3)	675	26.6	1755	69.1	500	73	15000	33100	22.00/3.0	TL	45.5	57.3
29.5R25	☆	3S	208	A2	TL	GL902(L-3)	770	30.3	1880	74.0	500	73	18000	38700	25.00/3.5	TL	50.0	63.0
EARTHMOVERS																		
13.00R25	☆☆☆	2S	163	B	TL	GL912(E-3)	354	13.9	1300	51.2	700	102	4875	10750	8.50	TL	24.5	30.9
14.00R25	☆☆☆	2S	182	A2	TT	GL912(E-3)	365	14.4	1365	53.7	950	138	8500	18740	10.00	TT	26.0	32.8
14.00R24	☆☆☆	2S	182	A2	TT	GL912(E-3)	365	14.4	1365	53.7	950	138	8500	18740	10.00	TT	26.0	32.8
14.00R24	☆☆	2S	168	B	TT/TL	GL982 (E-2)	376	14.8	1360	53.5	700	102	5600	12300	10.00W	TT/TL	28.5	35.9
18.00R25	☆☆	1S	185	B	TL	GL901 (E-3)	505	19.9	1622	63.9	700	102	9250	20400	13.00/2.5	TL	34.5	43.5
18.00R25	☆☆	1S	185	B	TT	GL901 (E-3)	505	19.9	1622	63.9	700	102	9250	20400	13.00/2.5	TT	34.5	43.5
23.5R25	☆☆	1S	185	B	TL	GL902(E-3)	617	24.3	1637	64.4	525	76	9250	20400	19.50/2.5	TL	40.0	50.4
23.5R25	☆☆	1S	185	B	TT	GL902(E-3)	617	24.3	1637	64.4	525	76	9250	20400	19.50/2.5	TT	40.0	50.4
26.5R25	☆☆	1S	193	B	TL	GL902(E-3)	675	26.6	1755	69.1	525	76	11500	25400	22.00/3.0	TL	45.5	57.3
29.5R25	☆☆	1S	200	B	TL	GL902(E-3)	770	30.3	1880	74.0	525	76	14000	30900	25.00/3.5	TL	50.0	63.0
29.5R25	☆☆	1S	200	B	TL	GL906(E-4)	770	30.3	1921	75.6	525	76	14000	30900	25.00/3.5	TL	57.0	71.8
18.00R25	☆☆	2S	185	B	TL	GL901 (E-3)	505	19.9	1622	63.9	700	102	9250	20400	13.00/2.5	TL	34.5	43.5
18.00R25	☆☆	2S	185	B	TT	GL901 (E-3)	505	19.9	1622	63.9	700	102	9250	20400	13.00/2.5	TT	34.5	43.5
20.5R25	☆☆	2S	177	B	TL	GL902(E-3)	532	20.9	1482	58.3	525	76	7300	16090	17.00/2.0	TL	33.0	41.6
23.5R25	☆☆	2S	185	B	TL	GL902(E-3)	617	24.3	1637	64.4	525	76	9250	20400	19.50/2.5	TL	40.0	50.4
23.5R25	☆☆	2S	185	B	TT	GL902(E-3)	617	24.3	1637	64.4	525	76	9250	20400	19.50/2.5	TT	40.0	50.4
26.5R25	☆☆	2S	193	B	TL	GL902(E-3)	675	26.6	1755	69.1	525	76	11500	25400	22.00/3.0	TL	45.5	57.3
29.5R25	☆☆	2S	200	B	TL	GL902(E-3)	770	30.3	1880	74.0	525	76	14000	30900	25.00/3.5	TL	50.0	63.0
29.5R25	☆☆	2S	200	B	TL	GL906(E-4)	770	30.3	1921	75.6	525	76	14000	30900	25.00/3.5	TL	57.0	71.8
650/65R25	☆☆	1S	169	A8	TL	GL906	640	25.2	1480	58.3	325	47	5800	12790	19.50/2.5	TL	41.0	51.7
650/65R25	☆	2S	169	A8	TL	GL906	640	25.2	1480	58.3	325	47	5800	12790	19.50/2.5	TL	41.0	51.7
IND-3																		
23.5R25	☆☆☆	—	208	A5	TL	GL902	622	24.5	1637	64.4	780	113	18000	38700	19.50/2.5	TL	41.0	51.7
26.5R25	☆☆	—	213	A5	TL	GL902	675	26.6	1755	69.1	690	100	20600	45400	22.00/3.0	TL	45.5	57.3
26.5R25	☆☆☆	—	217	A5	TL	GL902	675	26.6	1755	69.1	780	113	23000	50700	22.00/3.0	TL	45.5	57.3
29.5R25	☆☆☆	—	224	A5	TL	GL902	777	30.6	1881	74.1	780	113	28000	61500	25.00/3.5	TL	50.0	63.0
IND-4																		
29.5R25	☆☆☆	—	224	A5	TL	GL906	768	30.2	1803	71.0	780	113	28000	61500	25.00/3.5	TL	57.0	71.8
14.00R24	☆☆☆	—	193	A5	TT	GL907	382	15.0	1413	55.6	1000	145	12150	26800	10.0/10.00W	TT	63.0	79.4
18.00R25	☆☆☆	—	207	A5	TL	GL907	508	20.0	1655	65.2	1000	145	17500	38600	13.00/2.5	TL	34.5	43.5

COMPOUND CODE: 1S: STANDARD
2S: CUT-RESISTANT
3S: HEAT-RESISTANT

BIAS OTR TYRES

BIAS OTR (DUMPERS) TYRES FOR OPEN-PIT MINING SERVICE

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max.Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
	A3GG0040		16.00-25	28	B/*A2	TL	E-3J	430	16.9	1490	58.7	50/*10	30/*5	575/*750	83/*109	6700/*11500	14800/*25400	11.25	TL	28.5	35.9
	A3GG0041		16.00-25	32	B/*A2	TL	E-3J	430	16.9	1490	58.7	50/*10	30/*5	650/*875	94/*127	7300/*12500	16100/*27600	11.25	TL	28.5	35.9
	A3GG0042		16.00-25	36	B/*A2	TL	E-3J	430	16.9	1490	58.7	50/*10	30/*5	725/*975	105/*141	7750/*13600	17100/*30000	11.25	TL	28.5	35.9
		11AG0011	14.00-24	16	B/*A2	TT	E-3	375	14.8	1370	53.9	50/*10	30/*5	375/*550	54/*80	4000/*7300	8800/*16100	10.00	Z1-01-8	26.0	32.8
		11AG0013	14.00-24	20	B/*A2	TT	E-3	375	14.8	1370	53.9	50/*10	30/*5	475/*700	69/*102	4625/*8500	10200/*18700	10.00	Z1-01-8	26.0	32.8
		11AG0151	14.00-24	24	B/*A2	TT	E-3	375	14.8	1370	53.9	50/*10	30/*5	575/*850	83/*123	5150/*9500	11400/*20900	10.00	Z1-01-8	26.0	32.8
		11AG0009	13.00-25	26	B/*A2	TT	E-3	335	13.2	1300	51.2	50/*10	30/*5	650/*975	94/*141	4400/*5600	9700/*12300	8.5	Z1-01-8	27.0	34.0
		11AG0010	13.00-25	28	B/*A2	TT	E-3	335	13.2	1300	51.2	50/*10	30/*5	700/*1050	102/*152	4600/*5850	10150/*12900	8.5	Z1-01-8	27.0	34.0
A1UG0016 ①		A1AG0193	16.00-25	28	B/*A2	TL	E-3	430	16.9	1490	58.7	50/*10	30/*5	575/*750	83/*109	6700/*11500	14800/*25400	11.25	TL	28.5	35.9
A1TG0017		A1AG0192	16.00-25	32	B/*A2	TL	E-3	430	16.9	1490	58.7	50/*10	30/*5	650/*875	94/*127	7300/*12500	16100/*27600	11.25	TL	28.5	35.9
		11AG0029	16.00-25	24	B/*A2	TT	E-3	430	16.9	1490	58.7	50/*10	30/*5	475/*650	69/*94	6000/*10600	13200/*23400	11.25	Z1-01-8	28.5	35.9
		11AG0030	16.00-25	28	B/*A2	TT	E-3	430	16.9	1490	58.7	50/*10	30/*5	575/*750	83/*109	6700/*11500	14800/*25400	11.25	Z1-01-8	28.5	35.9
		A1AG0011	16.00-25	24	B/*A2	TL	E-3	430	16.9	1490	58.7	50/*10	30/*5	475/*650	69/*94	6000/*10600	13200/*23400	11.25	TL	28.5	35.9
		11AG0042	18.00-25	28	B/*A2	TT	E-3A	495	19.5	1615	63.6	50/*10	30/*5	500/*650	73/*94	8000/*13600	17600/*30000	13.00	Z1-01-8	30.0	37.8
	13GG0009	11AG0043	18.00-25	32	B/*A2	TT	E-3A	495	19.5	1615	63.6	50/*10	30/*5	575/*750	83/*109	8750/*15000	19300/*33100	13.00	Z1-01-8	30.0	37.8
		11AG0131	18.00-25	28	B/*A2	TL	E-3A	495	19.5	1615	63.6	50/*10	30/*5	500/*650	73/*94	8000/*13600	17600/*30000	13.00	TL	30.0	37.8
A3CG0010	A3GG0056	11AG0132	18.00-25	32	B/*A2	TL	E-3A	495	19.5	1615	63.6	50/*10	30/*5	575/*750	83/*109	8750/*15000	19300/*33100	13.00	TL	30.0	37.8
		11AG0124	18.00-25	36	B/*A2	TT	E-3A	495	19.5	1615	63.6	50/*10	30/*5	625/*850	91/*123	9250/*16000	20400/*35300	13.00	Z1-01-8	30.0	37.8
		11AG0133	18.00-25	36	B/*A2	TL	E-3A	495	19.5	1615	63.6	50/*10	30/*5	625/*850	91/*123	9250/*16000	20400/*35300	13.00	TL	30.0	37.8
		11AZK042	14.00-20	20	B	TT	E-3C	375	14.8	1266	49.8	50	30	770	111.7	5225	11519	10.00	Z1-01-8	25.0	31.5
		11AZK046	14.00-20	24	B	TT	E-3C+	375	14.8	1266	49.8	50	30	890	129.1	5600	12346	10.00	Z1-01-8	36.0	45.4
		11AZK034	14.00-20	24	B	TT	E-3C	375	14.8	1266	49.8	50	30	890	129.1	5600	12346	10.00	Z1-01-8	25.0	31.5
		11AG0149	13.00-25	28	B/*A2	TT	E-3C	340	13.4	1300	51.2	50	30	700	101.5	4600	10141	8.50	DG09C	26.0	32.8
		11AGK006	14.00-24	24	B/*A2	TT	E-3C	375	14.8	1370	53.9	50/*10	30/*5	575/*850	83/*123	5150/*9500	11400/*20900	10.00	Z1-01-8	26.5	33.4
		11AGK007	14.00-24	28	B/*A2	TT	E-3C	375	14.8	1370	53.9	50/*10	30/*5	650/*925	94/*134	5600/*10000	12300/*22000	10.00	Z1-01-8	26.5	33.4
		11AG0117	14.00-24	24	B/*A2	TT	E-3D	375	14.8	1370	53.9	50/*10	30/*5	575/*850	83/*123	5150/*9500	11400/*20900	10.00	Z1-01-8	30.0	37.8
		A1AG0031	18.00-25	32	B/*A2	TL	E-3G	495	19.5	1615	63.6	50/*10	30/*5	575/*750	83/*109	8750/*15000	19300/*33100	13.00	TL	35.0	44.1
		11AG0144	21.00-33	32	B	TT	E-3K	575	22.6	1970	77.6	50	30	500	73	10300	22700	15.00	Z1-01-10	36.5	46.0
		A1AG0152	14.00-24	24	B/*A2	TT	E-3L	375	14.8	1370	53.9	50/*10	30/*5	575/*850	83/*123	5150/*9500	11400/*20900	10.00	Z1-01-8	28.3	35.7



BIAS OTR TYRES

BIAS OTR (DUMPERS) TYRES FOR OPEN-PIT MINING SERVICE

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max.Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
		A1AGO185	14.00-24	28	B/*A2	TT	E-3L	375	14.8	1370	53.9	50/*10	30/*5	650/*925	94/*134	5600/*10000	12300/*22000	10.00	Z1-01-8	28.3	35.7
		A1AGO178	14.00-24	32	B/*A2	TT	E-3L	375	14.8	1370	53.9	50/*10	30/*5	725/*1000	105/*145	6000/*10500	13200/*23150	10.00	Z1-01-8	28.3	35.7
		A1AGO153	18.00-25	32	B/*A2	TT	E-3L	495	19.5	1615	63.6	50/*10	30/*5	575/*750	83/*109	8750/*15000	19300/*33100	13.00/2.5	Z1-01-8	33.1	41.7
	I3GG0011	A1AGO165	18.00-25	36	B/*A2	TT	E-3L	495	19.5	1615	63.6	50/*10	30/*5	625/*850	91/*123	9250/*16000	20400/*35300	13.00/2.5	Z1-01-8	33.1	41.7
		A1AGO163	18.00-33	32	B/*A2	TL	E-3L	495	19.5	1820	71.7	50/*10	30/*5	575/*750	83/*109	10000/*17500	22000/*38600	13.00/2.5	TL	34.0	42.8
	A3GG0073	I1AGO147	21.00-33	32	B	TT	E-3L	575	22.6	1970	77.6	50	30	500	73	10300	22700	15.00	Z1-01-10	36.5	46.0
	A3GG0074	A1AGO188	21.00-33	32	B	TL	E-3L	575	22.6	1970	77.6	50	30	500	73	10300	22700	15.00	Z1-01-10	36.5	46.0
		A1AGO195	24.00-35	48	B/*A2	TL	E-3L	650	25.6	2130	83.9	50/*10	30/*5	650/*850	94/*123	18500/*31500	40800/*69500	17.00/3.5	TL	41.1	51.8
A3CG0011①	A3GG0016	A1AGO040	18.00-33	32	B/*A2	TL	E-4	495	19.5	1875	73.8	50/*10	30/*5	575/*750	83/*109	10000/*17500	22000/*38600	13.00	TL	55.0	69.3
	A3GG0071	A1AGO042	18.00-33	36	B/*A2	TL	E-4	495	19.5	1875	73.8	50/*10	30/*5	625/*850	91/*123	10600/*18500	23400/*40800	13.00	TL	55.0	69.3
		I1AGO012	14.00-24	16	B/*A2	TT	E-4A	375	14.8	1370	53.9	50/*10	30/*5	375/*550	54/*80	4000/*7300	8800/*16100	10.00	Z1-01-8	30.0	37.8
	A3GG0076	I1AGO014	14.00-24	20	B/*A2	TT	E-4A	375	14.8	1370	53.9	50/*10	30/*5	475/*700	69/*102	4625/*8500	10200/*18700	10.00	Z1-01-8	30.0	37.8
		I1AGO016	14.00-24	24	B/*A2	TT	E-4A	375	14.8	1370	53.9	50/*10	30/*5	575/*850	83/*123	5150/*9500	11400/*20900	10.00	Z1-01-8	30.0	37.8
A31G0050	A3GG0069	A1AGO032	18.00-25	32	B/*A2	TL	E-4B	495	19.5	1675	65.9	50/*10	30/*5	575/*750	83/*109	8750/*15000	19300/*33100	13.00	TL	54.0	68.0
A31G0051	A3GG0070	I1AGO129	18.00-25	36	B/*A2	TL	E-4B	495	19.5	1675	65.9	50/*10	30/*5	625/*850	91/*123	9250/*16000	20400/*35300	13.00	TL	54.0	68.0
		A1AGO057	21.00-35	32	B/*A2	TL	E-4B	575	22.6	2050	80.7	50/*10	30/*5	500/*650	73/*94	12100/*21200	26700/*46700	15.00	TL	55.0	69.3
	A3GG0051	A1AGO058	21.00-35	36	B/*A2	TL	E-4B	575	22.6	2050	80.7	50/*10	30/*5	550/*750	80/*109	12850/*23000	28300/*50700	15.00	TL	55.0	69.3
	A3GG0015	A1AGO060	21.00-35	40	B/*A2	TL	E-4B	575	22.6	2050	80.7	50/*10	30/*5	625/*825	94/*120	14000/*24300	30900/*53600	15.00	TL	55.0	69.3
		A1AGO041	18.00-33	32	B/*A2	TL	E-4D	495	19.5	1875	73.8	50/*10	30/*5	575/*750	83/*109	10000/*17500	22000/*38600	13.00	TL	55.0	69.3
		A1AGO043	18.00-33	36	B/*A2	TL	E-4D	495	19.5	1875	73.8	50/*10	30/*5	625/*850	91/*123	10600/*18500	23400/*40800	13.00	TL	55.0	69.3
		A1AGO059	21.00-35	36	B/*A2	TL	E-4G	575	22.6	2050	80.7	50/*10	30/*5	550/*750	80/*109	12850/*23000	28300/*50700	15.00	TL	55.0	69.3
		A1AGO061	21.00-35	40	B/*A2	TL	E-4G	575	22.6	2050	80.7	50/*10	30/*5	625/*825	94/*120	14000/*24300	30900/*53600	15.00	TL	55.0	69.3
	A3GG0080	I1AGO106	21.00-35	36	B/*A2	TL	E-4H	575	22.6	2050	80.7	50/*10	30/*5	550/*750	80/*109	12850/*23000	28300/*50700	15.00	TL	42.0	52.9
		A1AGO201	21.00-35	40	B/*A2	TL	E-4H	575	22.6	2050	80.7	50/*10	30/*5	625/*825	94/*120	14000/*24300	30900/*53600	15.00	TL	42.0	52.9
		A1AGO148	24.00-35	42	B/*A2	TL	E-4J	650	25.6	2175	85.6	50/*10	30/*5	550/*750	80/*109	16500/*29000	36480/*64000	17.00/3.5	TL	62.7	79.0
	I3GG0010	A1AGO168	18.00-25	40	B/*A2	TT	E-4J	495	19.5	1675	65.9	50/*10	30/*5	700/*950	102/*138	9750/*17000	21500/*37500	13.00/2.5	Z1-01-8	56.3	70.9
		A1AGO156	18.00-33	32	B/*A2	TL	E-4J	495	19.5	1875	73.8	50/*10	30/*5	575/*750	83/*109	10000/*17500	22000/*38600	13.00	TL	55.1	69.4
		A1AGO200	18.00-33	36	B/*A2	TL	E-4J	495	19.5	1875	73.8	50/*10	30/*5	625/*850	91/*123	10600/*18500	23400/*40800	13.00/2.5	TL	55.1	69.4
		A1AGO199	18.00-33	40	B/*A2	TL	E-4J	495	19.5	1875	73.8	50/*10	30/*5	700/*950	102/*138	11200/*20000	24700/*44100	13.00/2.5	TL	55.1	69.4
	A3GG0104	A1AGO155	21.00-35	36	B/*A2	TL	E-4J	575	22.6	2050	80.7	50/*10	30/*5	550/*750	80/*109	12850/*23000	28300/*50700	15.00/3.0	TL	55.9	70.4
	A3GG0014		24.00-35	42	B/*A2	TL	E-4J	650	25.6	2175	85.6	50/*10	30/*5	550/*750	80/*109	16500/*29000	36480/*64000	17.00/3.5	TL	62.7	79.0

NOTE: ① More PART.No.s are: A3FG0002

BIAS OTR TYRES

BIAS OTR (DUMPERS) TYRES FOR OPEN-PIT MINING SERVICE

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max.Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
		A1AGO180	24.00-35	48	B/*A2	TL	E-4J	650	25.6	2175	85.6	50/*10	30/*5	650/*850	94/*123	18500/*31500	40800/*69500	17.00/3.5	TL	62.7	79.0
	A3GG0052	A1AGO177	27.00-49	48	B/*A2	TL	E-4J	737	29.0	2702	106.4	50/*10	30/*5	575/*775	83/*112	25000/*43750	55100/*96500	19.50/4.0	TL	63.5	80.0
		A1AGK002	33.00-51	58	B/*A2	TL	E-4J	894	35.2	3061	120.5	50/*10	30/*5	575/*750	83/*109	35500/*61500	78500/*135500	24.00	TL	88.3	111.2

BIAS OTR (LOADERS) TYRES FOR OPEN-PIT MINING SERVICE

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max. Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
	A3GG0020		15.5-25	12	B/*A2	TL	E-3J	395	15.6	1275	50.2	50/*10	30/*5	250/*400	36/*58	3250/*5600	7150/*12300	12.00	TL	25.0	31.5
	A3GG0027		17.5-25	12	B/*A2	TL	E-3J	445	17.5	1350	53.1	50/*10	30/*5	225/*350	33/*51	3650/*6150	8050/*13600	14.00	TL	30.0	37.8
	A3GG0029		17.5-25	16	B/*A2	TL	E-3J	445	17.5	1350	53.1	50/*10	30/*5	300/*475	44/*69	4250/*7300	9350/*16100	14.00	TL	30.0	37.8
	A3GG0031		17.5-25	20	B/*A2	TL	E-3J	445	17.5	1350	53.1	50/*10	30/*5	400/*575	58/*83	5000/*8250	11000/*18200	14.00	TL	30.0	37.8
	A3GG0033		17.5-25	24	A2	TT	E-3J	445	17.5	1350	53.1	10	5	675	98	9000	19800	14.00	TL	30.0	37.8
	A3GG0035		20.5-25	16	B/*A2	TL	E-3J	520	20.5	1490	58.7	50/*10	30/*5	275/*350	40/*51	5450/*8250	12000/*18200	17.00	TL	32.0	40.3
	A3GG0037		20.5-25	20	B/*A2	TL	E-3J	520	20.5	1490	58.7	50/*10	30/*5	325/*450	46/*65	6000/*9500	13200/*20900	17.00	TL	32.0	40.3
	A3GG0039		20.5-25	50	A2	TL	E-3J	520	20.5	1490	58.7	10	5	1030	149	15900	35000	17.00	TL	32.0	40.3
	A3GG0022		23.5-25	16	B/*A2	TL	E-3J	595	23.4	1615	63.6	50/*10	30/*5	225/*300	33/*44	6150/*9500	8050/*20900	19.50	TL	35.0	44.1
	A3GG0023		23.5-25	20	B/*A2	TL	E-3J	595	23.4	1615	63.6	50/*10	30/*5	300/*375	44/*54	7300/*10900	16100/*24000	19.50	TL	35.0	44.1
	A3GG0043		26.5-25	28	B/*A2	TL	E-3J	675	26.6	1750	68.9	50/*10	30/*5	350/*475	51/*69	10000/*15500	22000/*34200	22.00	TL	38.0	47.9
	A3GG0019		15.5-25	12	B/*A2	TL	L-2E	395	15.6	1275	50.2	50/*10	30/*5	250/*400	36/*58	3250/*5600	7150/*12300	12.00	TL	25.0	31.5
	A3GG0021		15.5-25	16	B/*A2	TL	L-2E	395	15.6	1275	50.2	50/*10	30/*5	325/*475	47/*69	3750/*6150	8250/*13600	12.00	TL	25.0	31.5
	A3GG0028		17.5-25	12	B/*A2	TL	L-2E	445	17.5	1350	53.1	50/*10	30/*5	225/*350	33/*51	3650/*6150	8050/*13600	14.00	TL	30.0	37.8
	A3GG0030		17.5-25	16	B/*A2	TL	L-2E	445	17.5	1350	53.1	50/*10	30/*5	300/*475	44/*69	4250/*7300	9350/*16100	14.00	TL	30.0	37.8
	A3GG0032		17.5-25	20	B/*A2	TL	L-2E	445	17.5	1350	53.1	50/*10	30/*5	400/*575	58/*83	5000/*8250	11000/*18200	14.00	TL	30.0	37.8
	A3GG0034		20.5-25	12	B/*A2	TL	L-2E	520	20.5	1490	58.7	50/*10	30/*5	200/*250	29/*36	4500/*6700	9900/*14800	17.00	TL	28.5	35.9
	A3GG0036		20.5-25	16	B/*A2	TL	L-2E	520	20.5	1490	58.7	50/*10	30/*5	275/*350	40/*51	5450/*8250	12000/*18200	17.00	TL	28.5	35.9
	A3GG0038		20.5-25	20	B/*A2	TL	L-2E	520	20.5	1490	58.7	50/*10	30/*5	325/*450	46/*65	6000/*9500	13200/*20900	17.00	TL	28.5	35.9
	A3GG0024		23.5-25	12	B/*A2	TL	L-2E	595	23.4	1615	63.6	50/*10	30/*5	175/*225	25/*33	5300/*8000	11700/*17600	19.50	TL	30.5	38.4
	A3GG0025		23.5-25	16	B/*A2	TL	L-2E	595	23.4	1615	63.6	50/*10	30/*5	225/*300	33/*44	6150/*9500	8050/*20900	19.50	TL	30.5	38.4
	A3GG0026		23.5-25	20	B/*A2	TL	L-2E	595	23.4	1615	63.6	50/*10	30/*5	300/*375	44/*54	7300/*10900	16100/*24000	19.50	TL	30.5	38.4
		11AGY028	12.5-20	12	B/*A2	TT	E-2	370	14.6	1145	45.1	50/*10	30/*5	280/*320	41/*46	2340/*3200	5160/*7055	11.00	Z1-01-8	20.0	25.2
		11AGY005	12.5-20	16	B/*A2	TT	E-2	370	14.6	1145	45.1	50/*10	30/*5	420/*460	61/*67	3180/*4250	7010/*9350	11.00	Z1-01-8	20.0	25.2



BIAS OTR TYRES

BIAS OTR (LOADERS) TYRES FOR OPEN-PIR MINING SERVICE

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max.Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
		1IAGY006	12.5-20	18	B/*A2	TT	E-2	370	14.6	1145	45.1	50/*10	30/*5	530/*560	77/*81	3630/*4900	8000/*10800	11.00	Z1-01-8	20.0	25.2
		A1AGO189	16/70-20 (405/70-20)	10	B/*A2	TL	E-2H	407	16.0	1076	42.4	50/*10	30/*5	250/*325	36/*47	2400/*4200	5290/*9260	13.00	TL	22.0	27.7
	A3GGY005	1IAGY033	16/70-20 (405/70-20)	14	B/*A2	TL	E-2H	407	16.0	1076	42.4	50/*10	30/*5	350/*450	51/*65	2925/*5150	6450/*11400	13.00	TL	22.0	27.7
	A3GGY006	A1AGO135	16/70-24 (405/70-24)	14	B/*A2	TL	E-2H	407	16.0	1178	46.4	50/*10	30/*5	350/*450	51/*65	3375/*5650	7440/*12450	13.00	TL	30.0	37.8
		1IAGO024	15.5-25	12	B/*A2	TT	E-3/L-3	395	15.6	1275	50.2	50/*10	30/*5	250/*400	36/*58	3250/*5600	7150/*12300	12.00	Z1-01-8	25.0	31.5
		1IAGO025	15.5-25	16	B/*A2	TT	E-3/L-3	395	15.6	1275	50.2	50/*10	30/*5	325/*475	47/*69	3750/*6150	8250/*13600	12.00	Z1-01-8	25.0	31.5
	A3GG0105	A1AGO204	15.5-25	12	B/*A2	TL	E-3/L-3	395	15.6	1275	50.2	50/*10	30/*5	250/*400	36/*58	3250/*5600	7150/*12300	12.00	TL	25.0	31.5
		A1AGO207	15.5-25	16	B/*A2	TL	E-3/L-3	395	15.6	1275	50.2	50/*10	30/*5	325/*475	47/*69	3750/*6150	8250/*13600	12.00	TL	25.0	31.5
	A3GG0109	A1AGO209	17.5-25	12	B/*A2	TL	E-3/L-3	445	17.5	1350	53.1	50/*10	30/*5	225/*350	33/*51	3650/*6150	8050/*13600	14.00	TL	30.0	37.8
		1IAGO038	17.5-25	14	B/*A2	TT	E-3/L-3	445	17.5	1350	53.1	50/*10	30/*5	255/*400	37/*58	3900/*6700	8600/*14800	14.00	Z1-01-8	30.0	37.8
	A3GG0111	A1AGO211	17.5-25	16	B/*A2	TL	E-3/L-3	445	17.5	1350	53.1	50/*10	30/*5	300/*475	44/*69	4250/*7300	9350/*16100	14.00	Z1-01-8	30.0	37.8
		1IAGO075	17.5-25	20	B/*A2	TT	E-3/L-3	445	17.5	1350	53.1	50/*10	30/*5	400/*575	58/*83	5000/*8250	11000/*18200	14.00	TL	30.0	37.8
	A3GG0108	A1AGO208	17.5-25	12	B/*A2	TL	E-3/L-3	445	17.5	1350	53.1	50/*10	30/*5	225/*350	33/*51	3650/*6150	8050/*13600	14.00	TL	30.0	37.8
	A3GG0110	A1AGO210	17.5-25	16	B/*A2	TL	E-3/L-3	445	17.5	1350	53.1	50/*10	30/*5	300/*475	44/*69	4250/*7300	9350/*16100	14.00	TL	30.0	37.8
	A3GG0112	A1AGO212	17.5-25	20	B/*A2	TL	E-3/L-3	445	17.5	1350	53.1	50/*10	30/*5	400/*575	58/*83	5000/*8250	11000/*18200	14.00	TL	30.0	37.8
		A1AGO158	17.5-25	32	A2	TT	E-3/L-3	445	17.5	1350	53.1	10	5	825	120	10500	23100	14.00	TL	30.0	37.8
		1IAGO046	20.5-25	12	B/*A2	TT	E-3/L-3	520	20.5	1490	58.7	50/*10	30/*5	200/*250	29/*36	4500/*6700	9900/*14800	17.00	Z1-01-8	32.0	40.3
	A3GG0117	A1AGO102	20.5-25	16	B/*A2	TT	E-3/L-3	520	20.5	1490	58.7	50/*10	30/*5	275/*350	40/*51	5450/*8250	12000/*18200	17.00	Z1-01-8	32.0	40.3
		A1AGO052	20.5-25	18	B/*A2	TT	E-3/L-3	520	20.5	1490	58.7	50/*10	30/*5	300/*400	44/*58	5730/*8920	12600/*19700	17.00	Z1-01-8	32.0	40.3
		1IAGO049	20.5-25	20	B/*A2	TT	E-3/L-3	520	20.5	1490	58.7	50/*10	30/*5	325/*450	46/*65	6000/*9500	13200/*20900	17.00	Z1-01-8	32.0	40.3
		1IAGO051	20.5-25	24	B/*A2	TT	E-3/L-3	520	20.5	1490	58.7	50/*10	30/*5	400/*525	58/*76	6700/*10300	14800/*22700	17.00	Z1-01-8	32.0	40.3
		A1AGO046	20.5-25	12	B/*A2	TL	E-3/L-3	520	20.5	1490	58.7	50/*10	30/*5	200/*250	29/*36	4500/*6700	9900/*14800	17.00	TL	32.0	40.3
A1XGO001 ①		A1AGO113	20.5-25EM	16	B/*A2	TL	E-3/L-3	520	20.5	1490	58.7	50/*10	30/*5	275/*350	40/*51	5450/*8250	12000/*18200	17.00	TL	32.0	40.3
	A3GG0116	A1AGO215	20.5-25	16	B/*A2	TL	E-3/L-3	520	20.5	1490	58.7	50/*10	30/*5	275/*350	40/*51	5450/*8250	12000/*18200	17.00	TL	32.0	40.3
	A3GG0118	A1AGO216	20.5-25	20	B/*A2	TL	E-3/L-3	520	20.5	1490	58.7	50/*10	30/*5	325/*450	46/*65	6000/*9500	13200/*20900	17.00	TL	32.0	40.3
A1XGO002		A1AGO115	20.5-25EM	20	B/*A2	TL	E-3/L-3	520	20.5	1490	58.7	50/*10	30/*5	325/*450	46/*65	6000/*9500	13200/*20900	17.00	TL	32.0	40.3
		A1AGO056	20.5-25	24	B/*A2	TL	E-3/L-3	520	20.5	1490	58.7	50/*10	30/*5	400/*525	58/*76	6700/*10300	14800/*22700	17.00	TL	32.0	40.3
		A1AGO229	20.5-25	28	A2	TL	E-3/L-3	520	20.5	1490	20.5	10	5	625	91	11500	25353	17.00	TL	32.0	40.3
	A3GG0119		20.5-25	50	A2	TL	E-3/L-3	520	20.5	1490	20.5	10	5	1125	163	16200	35720	17.00	TL	32.0	40.3

NOTE: ① More PART.No.s are: A1SGO007



BIAS OTR TYRES

BIAS OTR (LOADERS) TYRES FOR OPEN-PIR MINING SERVICE

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max. Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
		1IAG0113	23.5-25	12	B/*A2	TT	E-3/L-3	595	23.4	1615	63.6	50/*10	30/*5	175/*225	25/*33	5300/*8000	11700/*17600	19.50	Z1-01-8	36.0	45.4
		1IAG0100	23.5-25	16	B/*A2	TT	E-3/L-3	595	23.4	1615	63.6	50/*10	30/*5	225/*300	33/*44	6150/*9500	8050/*20900	19.50	Z1-01-8	36.0	45.4
	A3GG0126	A1AGO068	23.5-25	16	B/*A2	TT	E-3/L-3	595	23.4	1615	63.6	50/*10	30/*5	225/*300	33/*44	6150/*9500	8050/*20900	19.50	Z1-01-8	35.0	44.1
		A1AGO108	23.5-25	20	B/*A2	TT	E-3/L-3	595	23.4	1615	63.6	50/*10	30/*5	300/*375	44/*54	7300/*10900	16100/*24000	19.50	Z1-01-8	35.0	44.1
	A3GG0013	A1AGO107	23.5-25	24	B/*A2	TT	E-3/L-3	595	23.4	1615	63.6	50/*10	30/*5	350/*475	51/*69	8000/*12500	17600/*27600	19.50	Z1-01-8	36.0	45.4
	A3GG0127	A1AGO223	23.5-25	16	B/*A2	TL	E-3/L-3	595	23.4	1615	63.6	50/*10	30/*5	225/*300	33/*44	6150/*9500	8050/*20900	19.50	TL	35.0	44.1
A1SG0008 ①		A1AGO092	23.5-25EM	16	B/*A2	TL	E-3/L-3	595	23.4	1615	63.6	50/*10	30/*5	225/*300	33/*44	6150/*9500	8050/*20900	19.50	TL	35.0	44.1
A1TGO008 ②		A1AGO071	23.5-25	20	B/*A2	TL	E-3/L-3	595	23.4	1615	63.6	50/*10	30/*5	300/*375	44/*54	7300/*10900	16100/*24000	19.50	TL	35.0	44.1
	A3GG0128	A1AGO224	23.5-25	20	B/*A2	TL	E-3/L-3	595	23.4	1615	63.6	50/*10	30/*5	300/*375	44/*54	7300/*10900	16100/*24000	19.50	TL	35.0	44.1
A1XGO004		A1AGO091	23.5-25EM	20	B/*A2	TL	E-3/L-3	595	23.4	1615	63.6	50/*10	30/*5	300/*375	44/*54	7300/*10900	16100/*24000	19.50	TL	35.0	44.1
	A3GG0129	A1AGO225	23.5-25	24	B/*A2	TL	E-3/L-3	595	23.4	1615	63.6	50/*10	30/*5	350/*475	51/*69	8000/*12500	17600/*27600	19.50	TL	35.0	44.1
		1IAG0114	23.5-25EM	24	B/*A2	TL	E-3/L-3	595	23.4	1615	63.6	50/*10	30/*5	350/*475	51/*69	8000/*12500	17600/*27600	19.50	TL	35.0	44.1
		A1AGO146	23.5-25	28	B/*A2	TL	E-3/L-3	595	23.4	1615	63.6	50/*10	30/*5	400/*550	58/*80	8750/*13600	19300/*30000	19.50	TL	36.0	45.4
		A1AGO132	15.5-25*	12	B/*A2	TL	L-3X	395	15.6	1275	50.2	50/*10	30/*5	250/*400	36/*58	3250/*5600	7150/*12300	12.00	TL	25.0	31.5
		A1AGO133	15.5-25*	16	B/*A2	TL	L-3X	395	15.6	1275	50.2	50/*10	30/*5	325/*475	47/*69	3750/*6150	8250/*13600	12.00	TL	25.0	31.5
		1IAG0072	17.5-25	12	B/*A2	TT	L-3X	445	17.5	1350	53.1	50/*10	30/*5	225/*350	33/*51	3650/*6150	8050/*13600	14.00	Z1-01-8	30.0	37.8
		1IAG0064	17.5-25	14	B/*A2	TT	L-3X	445	17.5	1350	53.1	50/*10	30/*5	255/*400	37/*58	3900/*6700	8600/*14800	14.00	Z1-01-8	30.0	37.8
		A1AGO109	17.5-25	16	B/*A2	TT	L-3X	445	17.5	1350	53.1	50/*10	30/*5	300/*475	44/*69	4250/*7300	9350/*16100	14.00	Z1-01-8	30.0	37.8
		1IAG0074	17.5-25	20	B/*A2	TT	L-3X	445	17.5	1350	53.1	50/*10	30/*5	400/*575	58/*83	5000/*8250	11000/*18200	14.00	Z1-01-8	30.0	37.8
A1TGO010		A1AGO018	17.5-25*	12	B/*A2	TL	L-3X	445	17.5	1350	53.1	50/*10	30/*5	225/*350	33/*51	3650/*6150	8050/*13600	14.00	TL	30.0	37.8
A1TGO011		A1AGO022	17.5-25*	16	B/*A2	TL	L-3X	445	17.5	1350	53.1	50/*10	30/*5	300/*475	44/*69	4250/*7300	9350/*16100	14.00	TL	30.0	37.8
A1TGO012		A1AGO026	17.5-25*	20	B/*A2	TL	L-3X	445	17.5	1350	53.1	50/*10	30/*5	400/*575	58/*83	5000/*8250	11000/*18200	14.00	TL	30.0	37.8
		1IAG0083	20.5-25	12	B/*A2	TT	L-3X	520	20.5	1490	58.7	50/*10	30/*5	200/*250	29/*36	4500/*6700	9900/*14800	17.00	Z1-01-8	32.0	40.3
		A1AGO050	20.5-25*	16	B/*A2	TT	L-3X	520	20.5	1490	58.7	50/*10	30/*5	275/*350	40/*51	5450/*8250	12000/*18200	17.00	Z1-01-8	32.0	40.3
		1IAG0084	20.5-25	18	B/*A2	TT	L-3X	520	20.5	1490	58.7	50/*10	30/*5	300/*400	44/*58	5730/*8920	12600/*19700	17.00	Z1-01-8	32.0	40.3
		1IAG0050	20.5-25	20	B/*A2	TT	L-3X	520	20.5	1490	58.7	50/*10	30/*5	325/*450	46/*65	6000/*9500	13200/*20900	17.00	Z1-01-8	32.0	40.3
		1IAG0085	20.5-25	24	B/*A2	TT	L-3X	520	20.5	1490	58.7	50/*10	30/*5	400/*525	58/*76	6700/*10300	14800/*22700	17.00	Z1-01-8	32.0	40.3
		A1AGO112	20.5-25	12	B/*A2	TL	L-3X	520	20.5	1490	58.7	50/*10	30/*5	200/*250	29/*36	4500/*6700	9900/*14800	17.00	TL	32.0	40.3
A1TGO013		A1AGO051	20.5-25*	16	B/*A2	TL	L-3X	520	20.5	1490	58.7	50/*10	30/*5	275/*350	40/*51	5450/*8250	12000/*18200	17.00	TL	32.0	40.3



BIAS OTR TYRES

BIAS OTR (LOADERS) TYRES FOR OPEN-PIR MINING SERVICE

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max.Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
AITG0014		A1AGO094	20.5-25EM	16	B/*A2	TL	L-3X	520	20.5	1490	58.7	50/*10	30/*5	275/*350	40/*51	5450/*8250	12000/*18200	17.00	TL	32.0	40.3
		A1AGO116	20.5-25*	20	B/*A2	TL	L-3X	520	20.5	1490	58.7	50/*10	30/*5	325/*450	46/*65	6000/*9500	13200/*20900	17.00	TL	32.0	40.3
		A1AGO095	20.5-25EM	20	B/*A2	TL	L-3X	520	20.5	1490	58.7	50/*10	30/*5	325/*450	46/*65	6000/*9500	13200/*20900	17.00	TL	32.0	40.3
		A1AGO118	20.5-25*	24	B/*A2	TL	L-3X	520	20.5	1490	58.7	50/*10	30/*5	400/*525	58/*76	6700/*10300	14800/*22700	17.00	TL	32.0	40.3
		11AGO087	23.5-25	16	B/*A2	TT	L-3X	595	23.4	1615	63.6	50/*10	30/*5	225/*300	33/*44	6150/*9500	8050/*20900	19.50	Z1-01-8	35.0	44.1
		11AGO088	23.5-25	20	B/*A2	TT	L-3X	595	23.4	1615	63.6	50/*10	30/*5	300/*375	44/*54	7300/*10900	16100/*24000	19.50	Z1-01-8	36.0	45.4
		11AGO090	23.5-25	24	B/*A2	TT	L-3X	595	23.4	1615	63.6	50/*10	30/*5	350/*475	51/*69	8000/*12500	17600/*27600	19.50	Z1-01-8	36.0	45.4
AITG0016		A1AGO067	23.5-25	16	B/*A2	TL	L-3X	595	23.4	1615	63.6	50/*10	30/*5	225/*300	33/*44	6150/*9500	8050/*20900	19.50	TL	35.0	44.1
		A1AGO120	23.5-25EM	16	B/*A2	TL	L-3X	595	23.4	1615	63.6	50/*10	30/*5	225/*300	33/*44	6150/*9500	8050/*20900	19.50	TL	35.0	44.1
AITG0015		A1AGO072	23.5-25	20	B/*A2	TL	L-3X	595	23.4	1615	63.6	50/*10	30/*5	300/*375	44/*54	7300/*10900	16100/*24000	19.50	TL	35.0	44.1
		A1AGO122	23.5-25EM	20	B/*A2	TL	L-3X	595	23.4	1615	63.6	50/*10	30/*5	300/*375	44/*54	7300/*10900	16100/*24000	19.50	TL	35.0	44.1
		A1AGO074	23.5-25	24	B/*A2	TL	L-3X	595	23.4	1615	63.6	50/*10	30/*5	350/*475	51/*69	8000/*12500	17600/*27600	19.50	TL	35.0	44.1
		A1AGO190	16/70-20	10	A2	TT	L-1A	410	16.1	1075	42.3	10	5	250/*325	36/*47	2400/*4200	5290/*9260	13.00	Z1-01-8	14.0	17.6
		11AGO002	16/70-20	12	A2	TT	L-1A	410	16.1	1075	42.3	10	5	400	58	4800	10600	13.00	Z1-01-8	14.0	17.6
		A1AGO100	16/70-20	14	A2	TT	L-1A	410	16.1	1075	42.3	10	5	350/*450	51/*65	2925/*5150	6450/*11400	13.00	Z1-01-8	14.0	17.6
		A1AGO164	16/70-20	14	A2	TL	L-1A	410	16.1	1075	42.3	10	5	350/*450	51/*65	2925/*5150	6450/*11400	13.00	TL	14.0	17.6
		11AGO091	16/70-20	16	A2	TT	L-1A	410	16.1	1075	42.3	10	5	400/*500	58/*73	3150/*5665	6950/*12500	13.00	Z1-01-8	14.0	17.6
		11AGO023	15.5-25	12	B/*A2	TT	L-2	395	15.6	1275	50.2	50/*10	30/*5	250/*400	36/*58	3250/*5600	7150/*12300	12.00	Z1-01-8	25.0	31.5
		11AGO026	15.5-25	20	B/*A2	TT	L-2	395	15.6	1275	50.2	50/*10	30/*5	400/*550	58/*80	4250/*6700	9350/*14800	12.00	TL	25.0	31.5
	A3GG0106	A1AGO205	15.5-25	12	B/*A2	TL	L-2	395	15.6	1275	50.2	50/*10	30/*5	250/*400	36/*58	3250/*5600	7150/*12300	12.00	TL	25.0	31.5
	A3GG0107	A1AGO206	15.5-25	16	B/*A2	TL	L-2	395	15.6	1275	50.2	50/*10	30/*5	325/*475	47/*69	3750/*6150	8250/*13600	12.00	TL	25.0	31.5
		A1AGO130	15.5-25	12	B/*A2	TL	L-2X	395	15.6	1275	50.2	50/*10	30/*5	250/*400	36/*58	3250/*5600	7150/*12300	12.00	TL	25.0	31.5
		A1AGO131	15.5-25	16	B/*A2	TL	L-2X	395	15.6	1275	50.2	50/*10	30/*5	325/*475	47/*69	3750/*6150	8250/*13600	12.00	TL	25.0	31.5
		11AGO036	17.5-25	12	B/*A2	TT	L-2A	445	17.5	1350	53.1	50/*10	30/*5	225/*350	33/*51	3650/*6150	8050/*13600	14.00	Z1-01-8	30.0	37.8
	A3GG0113	A1AGO213	17.5-25	12	B/*A2	TL	L-2A	445	17.5	1350	53.1	50/*10	30/*5	225/*350	33/*51	3650/*6150	8050/*13600	14.00	TL	30.0	37.8
		11AGO104	17.5-25	14	B/*A2	TT	L-2A	445	17.5	1350	53.1	50/*10	30/*5	255/*400	37/*58	3900/*6700	8600/*14800	14.00	Z1-01-8	30.0	37.8
		A1AGO023	17.5-25	16	B/*A2	TT	L-2A	445	17.5	1350	53.1	50/*10	30/*5	300/*475	44/*69	4250/*7300	9350/*16100	14.00	Z1-01-8	30.0	37.8
		11AGO081	17.5-25	20	B/*A2	TT	L-2A	445	17.5	1350	53.1	50/*10	30/*5	400/*575	58/*83	5000/*8250	11000/*18200	14.00	Z1-01-8	30.0	37.8
	A3GG0114	A1AGO214	17.5-25	16	B/*A2	TL	L-2A	445	17.5	1350	53.1	50/*10	30/*5	300/*475	44/*69	4250/*7300	9350/*16100	14.00	TL	30.0	37.8

BIAS OTR TYRES

BIAS OTR (LOADERS) TYRES FOR OPEN-PIT MINING SERVICE

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max. Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
	A3GG0115	11AGO040	17.5-25	20	B/*A2	TL	L-2A	445	17.5	1350	53.1	50/*10	30/*5	400/*575	58/*83	5000/*8250	11000/*18200	14.00	TL	30.0	37.8
	A3GG0120	A1AGO217	20.5-25	12	B/*A2	TL	L-2A	520	20.5	1490	58.7	50/*10	30/*5	200/*250	29/*36	4500/*6700	9900/*14800	17.00	TL	28.5	35.9
A1XG0007		A1AGO089	20.5-25EM	12	B/*A2	TL	L-2A	520	20.5	1490	58.7	50/*10	30/*5	200/*250	29/*36	4500/*6700	9900/*14800	17.00	TL	28.5	35.9
	A3GG0121	A1AGO218	20.5-25	16	B/*A2	TL	L-2A	520	20.5	1490	58.7	50/*10	30/*5	275/*350	40/*51	5450/*8250	12000/*18200	17.00	TL	28.5	35.9
		A1AGO114	20.5-25EM	16	B/*A2	TL	L-2A	520	20.5	1490	58.7	50/*10	30/*5	275/*350	40/*51	5450/*8250	12000/*18200	17.00	TL	28.5	35.9
	A3GG0122	A1AGO219	20.5-25	20	B/*A2	TL	L-2A	520	20.5	1490	58.7	50/*10	30/*5	325/*450	46/*65	6000/*9500	13200/*20900	17.00	TL	28.5	35.9
		A1AGO136	20.5-25EM	20	B/*A2	TL	L-2A	520	20.5	1490	58.7	50/*10	30/*5	325/*450	46/*65	6000/*9500	13200/*20900	17.00	TL	28.5	35.9
	A3GG0123	A1AGO220	23.5-25	12	B/*A2	TL	L-2A	595	23.4	1615	63.6	50/*10	30/*5	175/*225	25/*33	5300/*8000	11700/*17600	19.50	TL	30.5	38.4
A1XG0008		A1AGO087	23.5-25EM	12	B/*A2	TL	L-2A	595	23.4	1615	63.6	50/*10	30/*5	175/*225	25/*33	5300/*8000	11700/*17600	19.50	TL	30.5	38.4
		11AGO096	23.5-25	16	B/*A2	TT	L-2A	595	23.4	1615	63.6	50/*10	30/*5	225/*300	33/*44	6150/*9500	8050/*20900	19.50	Z1-01-8	30.5	38.4
		11AGO107	23.5-25	20	B/*A2	TT	L-2A	595	23.4	1615	63.6	50/*10	30/*5	300/*375	44/*54	7300/*10900	16100/*24000	19.50	Z1-01-8	30.5	38.4
	A3GG0124	A1AGO221	23.5-25	16	B/*A2	TL	L-2A	595	23.4	1615	63.6	50/*10	30/*5	225/*300	33/*44	6150/*9500	8050/*20900	19.50	TL	30.5	38.4
		A1AGO090	23.5-25EM	16	B/*A2	TL	L-2A	595	23.4	1615	63.6	50/*10	30/*5	225/*300	33/*44	6150/*9500	8050/*20900	19.50	TL	30.5	38.4
		11AGO115	23.5-25EM	20	B/*A2	TL	L-2A	595	23.4	1615	63.6	50/*10	30/*5	300/*375	44/*54	7300/*10900	16100/*24000	19.50	TL	30.5	38.4
	A3GG0125	A1AGO222	23.5-25	20	B/*A2	TL	L-2A	595	23.4	1615	63.6	50/*10	30/*5	300/*375	44/*54	7300/*10900	16100/*24000	19.50	TL	30.5	38.4
		11AGO079	17.5-25	12	B/*A2	TT	L-2AX	445	17.5	1350	53.1	50/*10	30/*5	225/*350	33/*51	3650/*6150	8050/*13600	14.00	Z1-01-8	30.0	37.8
		11AGO111	17.5-25	14	B/*A2	TT	L-2AX	445	17.5	1350	53.1	50/*10	30/*5	255/*400	37/*58	3900/*6700	8600/*14800	14.00	Z1-01-8	30.0	37.8
		11AGO080	17.5-25	20	B/*A2	TT	L-2AX	445	17.5	1350	53.1	50/*10	30/*5	400/*575	58/*83	5000/*8250	11000/*18200	14.00	Z1-01-8	30.0	37.8
		11AGO077	17.5-25	16	B/*A2	TT	L-2AX	445	17.5	1350	53.1	50/*10	30/*5	300/*475	44/*69	4250/*7300	9350/*16100	14.00	Z1-01-8	30.0	37.8
		A1AGO016	17.5-25	12	B/*A2	TL	L-2AX	445	17.5	1350	53.1	50/*10	30/*5	225/*350	33/*51	3650/*6150	8050/*13600	14.00	TL	30.0	37.8
		A1AGO020	17.5-25	16	B/*A2	TL	L-2AX	445	17.5	1350	53.1	50/*10	30/*5	300/*475	44/*69	4250/*7300	9350/*16100	14.00	TL	30.0	37.8
		A1AGO025	17.5-25	20	B/*A2	TL	L-2AX	445	17.5	1350	53.1	50/*10	30/*5	400/*575	58/*83	5000/*8250	11000/*18200	14.00	TL	30.0	37.8
		A1AGO045	20.5-25	12	B/*A2	TL	L-2AX	520	20.5	1490	58.7	50/*10	30/*5	200/*250	29/*36	4500/*6700	9900/*14800	17.00	TL	28.5	35.9
		A1AGO088	20.5-25EM	12	B/*A2	TL	L-2AX	520	20.5	1490	58.7	50/*10	30/*5	200/*250	29/*36	4500/*6700	9900/*14800	17.00	TL	28.5	35.9
		A1AGO093	20.5-25EM	16	B/*A2	TL	L-2AX	520	20.5	1490	58.7	50/*10	30/*5	275/*350	40/*51	5450/*8250	12000/*18200	17.00	TL	28.5	35.9
		A1AGO048	20.5-25	16	B/*A2	TL	L-2AX	520	20.5	1490	58.7	50/*10	30/*5	275/*350	40/*51	5450/*8250	12000/*18200	17.00	TL	28.5	35.9
		A1AGO117	20.5-25	20	B/*A2	TL	L-2AX	520	20.5	1490	58.7	50/*10	30/*5	325/*450	46/*65	6000/*9500	13200/*20900	17.00	TL	28.5	35.9
		A1AGO123	23.5-25	12	B/*A2	TL	L-2AX	595	23.4	1615	63.6	50/*10	30/*5	175/*225	25/*33	5300/*8000	11700/*17600	19.50	TL	30.5	38.4
		A1AGO119	23.5-25EM	12	B/*A2	TL	L-2AX	595	23.4	1615	63.6	50/*10	30/*5	175/*225	25/*33	5300/*8000	11700/*17600	19.50	TL	30.5	38.4



BIAS OTR TYRES

BIAS OTR (LOADERS) TYRES FOR OPEN-PIT MINING SERVICE

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max. Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
		A1AGO121	23.5-25EM	16	B/*A2	TL	L-2AX	595	23.4	1615	63.6	50/*10	30/*5	225/*300	33/*44	6150/*9500	8050/*20900	19.50	TL	30.5	38.4
		A1AGO065	23.5-25	16	B/*A2	TL	L-2AX	595	23.4	1615	63.6	50/*10	30/*5	225/*300	33/*44	6150/*9500	8050/*20900	19.50	TL	30.5	38.4
		11AGO097	23.5-25	16	B/*A2	TT	L-2AX	595	23.4	1615	63.6	50/*10	30/*5	225/*300	33/*44	6150/*9500	8050/*20900	19.50	Z1-01-8	30.5	38.4
		A1AGO070	23.5-25	20	B/*A2	TL	L-2AX	595	23.4	1615	63.6	50/*10	30/*5	300/*375	44/*54	7300/*10900	16100/*24000	19.50	TL	30.5	38.4
		11AGO001	16/70-20	10	B/*A2	TT	L-3A	410	16.1	1075	42.3	50/*10	30/*5	250/*325	36/*47	2400/*4200	5290/*9260	13.00	Z1-01-8	25.0	31.5
		11AGO004	16/70-20	14	B/*A2	TT	L-3A	410	16.1	1075	42.3	50/*10	30/*5	350/*450	51/*65	2925/*5150	6450/*11400	13.00	Z1-01-8	25.0	31.5
		11AGO005	16/70-20	16	B/*A2	TT	L-3A	410	16.1	1075	42.3	50/*10	30/*5	400/*500	58/*73	3150/*5665	6950/*12500	13.00	Z1-01-8	25.0	31.5
A1SG0001		A1AGO143	16/70-20	14	B/*A2	TL	L-3A	410	16.1	1075	42.3	50/*10	30/*5	350/*450	51/*65	2925/*5150	6450/*11400	13.00	TL	25.0	31.5
		11AGO006	16/70-20	16	B/*A2	TL	L-3A	410	16.1	1075	42.3	50/*10	30/*5	400/*500	58/*73	3150/*5665	6950/*12500	13.00	TL	25.0	31.5
		11AGO034	16/70-24	10	B/*A2	TT	L-3A	475	18.7	1175	46.3	50/*10	30/*5	250/*325	36/*47	2775/*4750	6100/*10500	13.00	Z1-01-8	24.0	30.2
		11AGO035	16/70-24	14	B/*A2	TT	L-3A	475	18.7	1175	46.3	50/*10	30/*5	350/*450	51/*65	3375/*5650	7450/*12500	13.00	Z1-01-8	24.0	30.2
		A1AGO013	16/70-24	10	B/*A2	TL	L-3A	475	18.7	1175	46.3	50/*10	30/*5	250/*325	36/*47	2775/*4750	6100/*10500	13.00	TL	24.0	30.2
A1SG0004		A1AGO014	16/70-24	14	B/*A2	TL	L-3A	475	18.7	1175	46.3	50/*10	30/*5	350/*450	51/*65	3375/*5650	7450/*12500	13.00	TL	24.0	30.2
		11AGO136	17.5-25	12	B/*A2	TT	L-3C	445	17.5	1350	53.1	50/*10	30/*5	225/*350	33/*51	3650/*6150	8050/*13600	14.00	Z1-01-8	30.0	37.8
		11AGO142	20.5-25	16	B/*A2	TT	L-3C	520	20.5	1490	58.7	50/*10	30/*5	275/*350	40/*51	5450/*8250	12000/*18200	17.00	Z1-01-8	32.0	40.3
		11AGO045	20.5-25	20	B/*A2	TT	L-3C	520	20.5	1490	58.7	50/*10	30/*5	325/*450	46/*65	6000/*9500	13200/*20900	17.00	Z1-01-8	32.0	40.3
		11AGO135	23.5-25	16	B/*A2	TT	L-3C	595	23.4	1615	63.6	50/*10	30/*5	225/*300	33/*44	6150/*9500	8050/*20900	19.50	Z1-01-8	35.0	44.1
		11AGO145	23.5-25	20	B/*A2	TT	L-3C	595	23.4	1615	63.6	50/*10	30/*5	300/*375	44/*54	7300/*10900	16100/*24000	19.50	Z1-01-8	35.0	44.1
		A1AGO161	17.5-25	12	B/*A2	TL	L-3D	445	17.5	1350	53.1	50/*10	30/*5	225/*350	33/*51	3650/*6150	8050/*13600	14.00	TL	25.4	32.0
A3CG0019		A1AGO075	26.5-25	20	B/*A2	TL	E-3/L-3	675	26.6	1750	68.9	50/*10	30/*5	250/*350	36/*51	8250/*13200	18200/*29100	22.00	TL	38.0	47.9
A3CG0020		A1AGO076	26.5-25	24	B/*A2	TL	E-3/L-3	675	26.6	1750	68.9	50/*10	30/*5	300/*400	44/*58	9250/*14000	20400/*30900	22.00	TL	38.0	47.9
		A1AGO077	26.5-25	26	B/*A2	TL	E-3/L-3	675	26.6	1750	68.9	50/*10	30/*5	325/*450	47/*65	9500/*15000	20900/*33100	22.00	TL	38.0	47.9
		A1AGO226	26.5-25	28	B/*A2	TL	E-3/L-3	675	26.6	1750	68.9	50/*10	30/*5	350/*475	51/*69	10000/*15500	22000/*34200	22.00	TL	38.0	47.9
		A1AGO159	26.5-25	32	B/*A2	TL	E-3/L-3	675	26.6	1750	68.9	50/*10	30/*5	425/*550	62/*80	11200/*17000	24700/*37500	22.00	TL	38.0	47.9
		A1AGO151	26.5-25	44	B/*A2	TL	E-3/L-3	675	26.6	1750	68.9	50/*10	30/*5	*775	*112	*20800	*45800	22.00	TL	38.0	47.9
	A3GG0058	A1AGO080	29.5-25	22	B/*A2	TL	E-3/L-3	750	29.5	1875	73.8	50/*10	30/*5	250/*325	36/*46	10000/*15000	22000/*34200	25.00	TL	41.0	51.7
		A1AGO126	29.5-25	22	B/*A2	TL	E-3/L-3	750	29.5	1875	73.8	50/*10	30/*5	250/*325	36/*46	10000/*15000	22000/*34200	25.00	TL	41.0	51.7
A3CG0021	A3GG0059	A1AGO081	29.5-25	28	B/*A2	TL	E-3/L-3	750	29.5	1875	73.8	50/*10	30/*5	325/*425	46/*62	11500/*17500	25400/*38600	25.00	TL	41.0	51.7
A4FG0001		A1AGO124	29.5-25	28	B/*A2	TL	E-3/L-3	750	29.5	1875	73.8	50/*10	30/*5	325/*425	46/*62	11500/*17500	25400/*38600	25.00	TL	41.0	51.7



BIAS OTR TYRES

BIAS OTR (LOADERS) TYRES FOR OPEN-PIT MINING SERVICE

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max.Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
		A1AGO129	29.5-25	34	B/*A2	TL	E-3/L-3	750	29.5	1875	73.8	50/*10	30/*5	400/*525	58/*76	12950/*19800	28500/*43600	25.00	TL	41.0	51.7
		A1AGO203	33.25-29	32	B/*A2	TL	E-3/L-3	845	33.3	2090	82.3	50/*10	30/*5	325/*450	47/*65	15000/*23600	33100/*52000	27.00	TL	42.5	53.5
		A1AGO202	33.25-29	38	B/*A2	TL	E-3/L-3	845	33.3	2090	82.3	*10	*5	*525	*76	*25750	*56800	27.00	TL	42.5	53.5
A3CG0022	A3GG0061	A1AGO082	29.5-29	22	B/*A2	TL	L-3B	750	29.5	1975	77.8	50/*10	30/*5	250/*325	36/*46	10600/*16000	23400/*35300	25.00	TL	41.0	51.7
A3CG0023	A3GG0062	A1AGO083	29.5-29	28	B/*A2	TL	L-3B	750	29.5	1975	77.8	50/*10	30/*5	325/*425	46/*62	12150/*19000	26800/*41900	25.00	TL	41.0	51.7
		A1AGO145	29.5-29	34	B/*A2	TL	L-3B	750	29.5	1975	77.8	50/*10	30/*5	400/*525	58/*76	14000/*21200	30900/*46700	25.00	TL	41.0	51.7
		A1AGO231	29.5-29	40	B/*A2	TL	L-3B	750	29.5	1975	77.8	50/*10	30/*5	475/*625	69/*90	15000/*23600	33100/*52030	25.00	TL	41.0	51.7
		A1AGO134	26.5-25	20	B/*A2	TL	L-3X	675	26.6	1750	68.9	50/*10	30/*5	250/*350	36/*51	8250/*13200	18200/*29100	22.00	TL	38.0	47.9
		11AGO138	26.5-25	24	B/*A2	TL	L-3X	675	26.6	1750	68.9	50/*10	30/*5	300/*400	44/*58	9250/*14000	20400/*30900	22.00	TL	38.0	47.9
A1TGO020	A3GG0083	A1AGO171	20.5-25	16	A2	TL	L-5	520	20.5	1548	60.9	10	5	350	51	8250	18200	17.00/2.0	TL	80.0	100.8
	A3GG0063		20.5-25	20	A2	TT	L-5	520	20.5	1548	60.9	10	5	450	65	9500	20900	17.00/2.0	TL	80.0	100.8
		A1AGO173	23.5-25	16	A2	TL	L-5	595	23.4	1673	65.9	10	5	300	44	9500	20900	19.00/2.5	TL	90.0	113.4
A1TGO021	A3GG0064	A1AGO187	23.5-25	20	A2	TL	L-5	595	23.4	1673	65.9	10	5	375	54	10900	24000	19.00/2.5	TL	90.0	113.4
		A1AGO197	23.5-25	40	A2	TL	L-5	595	23.4	1673	65.9	10	5	800	116	17000	37400	19.00/2.5	TL	90.0	113.4
	A3GG0082	A1AGO175	26.5-25	20	A2	TL	L-5	675	26.6	1798	70.8	10	5	350	51	13200	29100	22.00/3.0	TL	100.0	126.0
		A1AGO186	26.5-25	28	A2	TL	L-5	675	26.6	1798	70.8	10	5	475	69	15500	34200	22.00/3.0	TL	100.0	126.0
	A3GG0075	A1AGO181	29.5-25	28	A2	TL	L-5	750	29.5	1923	75.7	10	5	425	62	17500	38600	25.00/3.5	TL	110.0	138.6
		A1AGO179	35/65-33	30	A2	TL	L-5	889	35.0	2077	81.8	10	5	450	65	21800	48100	28.00/3.5	TL	82.0	103.3
		A1AGO183	35/65-33	42	A2	TL	L-5	889	35.0	2077	81.8	10	5	575	83	25000	55100	28.00/3.5	TL	82.0	103.3

BIAS OTR TYRES FOR UNDERGROUND MINING SERVICE

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max.Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
			16.00-25	28	A2	TL	L-5SB	430	16.9	1550	61.0	10	5	750	109	11500	25400	11.25	TL	51.0	64.3
			16.00-25	32	A2	TL	L-5SB	430	16.9	1550	61.0	10	5	875	127	12500	27600	11.25	TL	51.0	64.3
			16.00-25	36	A2	TL	L-5SB	430	16.9	1550	61.0	10	5	975	141	13600	30000	11.25	TL	51.0	64.3
			23.5-25	32	A2	TL	L-5SB	595	23.4	1675	65.9	10	5	625	91	14650	32300	19.50	TL	105.0	132.3
			23.5-25	50	A2	TL	L-6S	595	23.4	1675	65.9	10	5	975	141	19000	41900	19.50	TL	105.0	132.3
		11AGG148	14.00-24*	24	A2	TT	L-4S	375	14.8	1420	55.9	10	5	850	123	9500	20900	10.00	Z1-01-8	45.5	57.3



BIAS OTR TYRES

BIAS OTR TYRES FOR UNDERGROUND MINING SERVICE

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max.Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
		11AGG004	14.00-24	24	A2	TT	L-3S	375	14.8	1420	55.9	10	5	850	123	9500	20900	10.00	Z1-01-8	43.0	54.2
	A3GGG009	11AGG003	14.00-24	24	A2	TT	L-5S	375	14.8	1420	55.9	10	5	850	123	9500	20900	10.00	Z1-01-8	63.5	80.0
	A3GGG010	11AGG001	14.00-24	28	A2	TT	L-5S	375	14.8	1420	55.9	10	5	925	134	10000	22000	10.00	Z1-01-8	63.5	80.0
		A1AGG002	18.00-25	28	A2	TL	L-5S	495	19.5	1675	65.9	10	5	650	94	13600	30000	13.00	TL	78.5	98.9
	A3GGG004	A1AGG003	18.00-25	32	A2	TL	L-5S	495	19.5	1675	65.9	10	5	750	109	15000	33100	13.00	TL	78.5	98.9
		A1AGG010	18.00-25	32	A2	TL	L-5SA	495	19.5	1675	65.9	10	5	750	109	15000	33100	13.00	TL	78.0	98.3
		11AGG002	17.5-25	20	A2	TT	L-5S	445	17.5	1400	55.1	10	5	575	83	8250	18200	14.00	Z1-01-8	63.5	80.0
		A1AGG001	17.5-25	20	A2	TL	L-5S	445	17.5	1400	55.1	10	5	575	83	8250	18200	14.00	TL	63.5	80.0
	A3GGG002	A1AGG032	17.5-25	24	A2	TL	L-5S	445	17.5	1400	55.1	10	5	675	98	9000	19800	14.00	TL	63.5	80.0
	A3GGG003	A1AGG026	20.5-25	24	A2	TL	L-5S	520	20.5	1550	61.0	10	5	525	76	10300	22700	17.00	TL	63.0	79.4
	A3GGG006	A1AGG036	26.5-25	28	A2	TL	L-5S	675	26.6	1795	70.7	10	5	475	69	15500	34200	22.00	TL	87.5	110.2
	A3GGG007	A1AGG009	26.5-25	32	A2	TL	L-5S	675	26.6	1795	70.7	10	5	550	80	17000	37500	22.00	TL	87.5	110.2
	A3GGG008	A1AGG007	26.5-25	36	A2	TL	L-5S	675	26.6	1795	70.7	10	5	625	91	18300	40350	22.00	TL	87.5	110.2
	A3GGG013	A1AGG012	26.5-25	32	A2	TL	L-6S	675	26.6	1795	70.7	10	5	550	80	17000	37500	22.00	TL	87.0	110.2
	A3GGG011	A1AGG033	26.5-25	50	A2	TL	L-6S	675	26.6	1795	70.7	10	5	850	123	22000	48500	22.00	TL	87.5	110.2

BIAS OTR TYRES FOR PORT SERVICE

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max.Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
		11AGO063	14.00-24	24	B/*A2	TT	L-1	375	14.8	1370	53.9	50/*10	30/*5	575/*850	83/*123	5150/*9500	11400/*20900	10.00	Z1-01-8	25.0	31.5
		11AGO020	14.00-24	28	B/*A2	TT	L-1	375	14.8	1370	53.9	50/*10	30/*5	650/*925	94/*134	5600/*10000	12300/*22000	10.00	Z1-01-8	25.0	31.5
		A1AGO038	18.00-25	44	B/*A2	TL	E-1	495	19.5	1615	63.6	50/*10	30/*5	775/*1050	112/*152	10400/*18000	23000/*39700	13.00	TL	28.5	35.9
	A3GGO060	11AGO015	14.00-24	24	B/*A2	TT	E-3	375	14.8	1370	53.9	50/*10	30/*5	575/*850	83/*123	5150/*9500	11400/*20900	10.00	Z1-01-8	26.0	32.8
		11AGO018	14.00-24	28	B/*A2	TT	E-3	375	14.8	1370	53.9	50/*10	30/*5	650/*925	94/*134	5600/*10000	12300/*22000	10.00	Z1-01-8	26.0	32.8
		11AGO137	14.00-24	32	B/*A2	TT	E-3	375	14.8	1370	53.9	50/*10	30/*5	725/*1000	105/*145	6000/*10500	13200/*23150	10.00	Z1-01-8	26.0	32.8
		11AGO105	16.00-25	32	B/*A2	TT	E-3	430	16.9	1490	58.7	50/*10	30/*5	650/*875	94/*127	7300/*12500	16100/*27600	11.25	Z1-01-8	28.5	35.9
		11AGO150	16.00-25	36	B/*A2	TT	E-3	430	16.9	1490	58.7	50/*10	30/*5	725/*975	105/141	7750/*13600	17100/*30000	11.25	Z1-01-8	28.5	35.9
		A1AGO012	16.00-25	28	B/*A2	TL	E-3	430	16.9	1490	58.7	50/*10	30/*5	575/*750	83/*109	6700/*11500	14800/*25400	11.25	TL	28.5	35.9
	A3GGO050	11AGO032	16.00-25	32	B/*A2	TL	E-3	430	16.9	1490	58.7	50/*10	30/*5	650/*875	94/*127	7300/*12500	16100/*27600	11.25	TL	28.5	35.9
		11AGO146	16.00-25	36	B/*A2	TL	E-3	430	16.9	1490	58.7	50/*10	30/*5	725/*975	105/141	7750/*13600	17100/*30000	11.25	TL	28.5	35.9

BIAS OTR TYRES

BIAS OTR TYRES FOR PORT SERVICE

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max. Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
A3EGO001		11AGO125	18.00-25	40	B/*A2	TT	E-3A	495	19.5	1615	63.6	50/*10	30/*5	700/*950	102/*138	9750/*17000	21500/*37500	13.00	Z1-01-8	30.0	37.8
	A3GGO072	11AGO134	18.00-25	40	B/*A2	TL	E-3A	495	19.5	1615	63.6	50/*10	30/*5	700/*950	102/*138	9750/*17000	21500/*37500	13.00	TL	30.0	37.8
		A1AGO039	18.00-25	44	B/*A2	TL	E-3A	495	19.5	1615	63.6	10	5	775/*1050	112/*152	10400/*18000	23000/*39700	13.00	TL	30.0	37.8
		11AGO126	18.00-25	40	B/*A2	TT	E-3G	495	19.5	1615	63.6	50/*10	30/*5	700/*950	102/*138	9750/*17000	21500/*37500	13.00	Z1-01-8	35.0	44.1
		11AGO128	18.00-25	40	B/*A2	TL	E-3G	495	19.5	1615	63.6	50/*10	30/*5	700/*950	102/*138	9750/*17000	21500/*37500	13.00	TL	35.0	44.1
		11AGO127	18.00-25	44	B/*static	TL	E-3G	495	19.5	1615	63.6	50/*10	30/*5	*1050/1050	152/*152	*18000/28800	39700/*63500	13.00	TL	35.0	44.1
	A3GGO079	A1AGO172	18.00-25	40	B/*A2	TL	E-3L	495	19.5	1615	63.6	50/*10	30/*5	700/*950	102/*138	9750/*17000	21500/*37500	13.00/2.5	TL	31.5	39.7
		A1AGO227	18.00-25	48	B/*A2	TL	E-3L	495	19.5	1615	63.6	50/*10	30/*5	1150	167	19000	41800	13.00/2.5	TL	31.5	39.7
	A3GGO005	A1AGO160	21.00-25	40	B/*A2	TL	E-3L	575	22.6	1750	68.9	50/*10	30/*5	625/*825	91/*120	11700/*20100	25800/*44300	15.00/3.0	TL	42.5	53.5
	A3GGO006	A1AGO150	21.00-35	40	B/*A2	TL	E-3L	575	22.6	2005	78.9	50/*10	30/*5	625/*825	94/*120	14000/*24300	30900/*53600	15.00/3.0	TL	39.4	49.6
	A3GGO011	A1AGO162	24.00-35	42	B/*A2	TL	E-3L	650	25.6	2130	83.9	50/*10	30/*5	550/*750	83/*109	17000/*29000	37500/*64000	17.00/3.5	TL	41.1	51.8
	A3GGO078	A1AGO198	24.00-35	48	B/*A2	TL	E-3L	650	25.6	2130	83.9	50/*10	30/*5	650/850	94.3/123.3	18500/*31500	40700/*63000	17.00/3.5	TL	41.1	51.8
	A3GGO008	A1AGO174	21.00-25	40	B/*A2	TL	E-3LA	575	22.6	1750	68.9	50/*10	30/*5	625/*825	91/*120	11700/*20100	25800/*44300	15.00/3.0	TL	29.9	37.7
	A3GGO007		21.00-35	40	B/*A2	TL	E-3LA	575	22.6	2005	78.9	50/*10	30/*5	625/*825	94/*120	14000/*24300	30900/*53600	15.00/3.0	TL	29.6	37.3
		11AGO031	16.00-25	28	B/*A2	TT	E-4	430	16.9	1545	60.8	50/*10	30/*5	575/*750	83/*109	6700/*11500	14800/*25400	11.25	Z1-01-8	51.5	64.9
	13GGO007	11AGO139	16.00-25	32	B/*A2	TT	E-4	430	16.9	1545	60.8	50/*10	30/*5	650/*875	94/*127	7300/*12500	16100/*27600	11.25	Z1-01-8	51.5	64.9
		11AGO152	16.00-25	36	B/*A2	TT	E-4	430	16.9	1545	60.8	10	5	975	141	13600	29920	11.25	Z1-01-8	51.5	64.9
			16.00-25	36	B/*A2	TL	E-4J	430	16.9	1545	60.8	10	5	975	141	13600	29920	11.25	TL	51.5	64.9
A4FGO003		A1AGO166	18.00-25	40	B/*A2	TL	E-4	495	19.5	1675	65.9	50/*10	30/*5	700/*950	102/*138	9750/*17000	21500/*37500	13.00	TL	54.0	68.0
		11AGO118	14.00-24	20	B/*A2	TT	E-4A	375	14.8	1370	53.9	50/*10	30/*5	475/*700	69/*102	4625/*8500	10200/*18700	10.00	Z1-01-8	30.0	37.8
	13GGO005	11AGO119	14.00-24	24	B/*A2	TT	E-4A	375	14.8	1370	53.9	50/*10	30/*5	575/*850	83/*123	5150/*9500	11400/*20900	10.00	Z1-01-8	30.0	37.8
A4MGO002	13GGO006	11AGO120	14.00-24	28	B/*A2	TT	E-4A	375	14.8	1370	53.9	50/*10	30/*5	650/*925	94/*134	5600/*10000	12300/*22000	10.00	Z1-01-8	30.0	37.8
	13GGO008	11AGO121	14.00-24	32	B/*A2	TT	E-4A	375	14.8	1370	53.9	50/*10	30/*5	725/*1000	105/*145	6000/*10500	13200/*23150	10.00	Z1-01-8	30.0	37.8
		A1AGO184	18.00-25	32	B/*A2	TL	E-4B	495	19.5	1675	65.9	50/*10	30/*5	575/*750	83/*109	8750/*15000	19300/*33100	13.00	TL	54.0	68.0
A4FGO002 ①	13GGO004	11AGO130	18.00-25	40	B/*A2	TL	E-4B	495	19.5	1675	65.9	50/*10	30/*5	700/*950	102/*138	9750/*17000	21500/*37500	13.00	TL	54.0	68.0
		A1AGO154	18.00-25	44	B/*A2	TL	E-4B	495	19.5	1675	65.9	50/*10	30/*5	775/*1050	112/*152	10400/*18000	23000/*39700	13.00	TL	54.0	68.0
		11AGO017	14.00-24	24	B/*A2	TT	E-4C	375	14.8	1420	55.9	50/*10	30/*5	575/*850	83/*123	5150/*9500	11400/*20900	10.00	Z1-01-8	45.5	57.3
	A4MGO004	11AGO099	14.00-24	28	B/*A2	TT	E-4C	375	14.8	1420	55.9	50/*10	30/*5	650/*925	94/*134	5600/*10000	12300/*22000	10.00	Z1-01-8	45.5	57.3
		A1AGO147	18.00-33	40	B/*A2	TL	E-4D	495	19.5	1875	73.8	50/*10	30/*5	700/*950	102/*138	11200/*20000	24700/*44100	13.00	TL	55.0	69.3



BIAS OTR TYRES

BIAS OTR TYRES FOR PORT SERVICE

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max.Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
		11AGO154	14.00-24	28	B/*A2	TT	E-4J	375	14.8	1370	53.9	50/*10	30/*5	650/*925	94/*134	5600/*10000	12300/*22000	10.00	Z1-01-8	45.5	57.3
		11AGO153	18.00-25	40	B/*A2	TT	E-4J	495	19.5	1675	65.9	50/*10	30/*5	700/*950	102/*138	9750/*17000	21500/*37500	13.00/2.5	Z1-01-8	56.3	70.9
A4MGO003		A1AGO157	18.00-25	40	B/*A2	TL	E-4J	495	19.5	1675	65.9	50/*10	30/*5	700/*950	102/*138	9750/*17000	21500/*37500	13.00/2.5	TL	56.3	70.9
		A1AGO199	18.00-33	40	B/*A2	TL	E-4J	495	19.5	1875	73.8	50/*10	30/*5	700/*950	102/*138	11200/*20000	24700/*44100	13.00/2.5	TL	55.1	69.4
		A1AGO228	18.00-25	40	B/*A2	TT	IND-4	500	19.7	1675	65.9	10	5	950	138	17000	37400	13.00	Z1-01-8	64.0	80.6
		A1AGG006	18.00-25	40	A2	TL	L-4S	495	19.5	1675	65.9	10	5	950	138	17000	37500	13.00	TL	78.5	98.9
A4FGG001	A3GGG001	A1AGG037	18.00-25	40	A2	TL	L-4SA	495	19.5	1675	65.9	10	5	950	138	17000	37500	13.00	TL	78.5	98.9
A2AGG001	A3GGG005	A1AGG004	18.00-25	40	A2	TL	L-5S	495	19.5	1675	65.9	10	5	950	138	17000	37500	13.00	TL	78.5	98.9

BIAS OTR (GRADERS) TYRES

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max.Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
A31G0047	A3GG0049		13.00-24	14	A8/*A2	TL	G-2A	335	13.2	1275	50.2	40/*10	25/*5	350/*525	51/*76	3000/*6150	6600/*13600	8.00TG	TL	23.0	29.0
A31G0049	A3GG0046		14.00-24	16	A8/*A2	TL	G-2A	360	14.2	1345	53.0	40/*10	25/*5	350/*550	51/*80	3650/*7300	8050/*16100	8.00TG	TL	24.0	30.2
A31G0046	A3GG0044		13.00-24	12	A8/*A2	TL	G-2A	335	13.2	1275	50.2	40/*10	25/*5	300/*450	44/*65	2725/*5600	6000/*12300	8.00TG	TL	23.0	29.0
A31G0048	A3GG0045		14.00-24	12	A8/*A2	TL	G-2A	360	14.2	1345	53.0	40/*10	25/*5	250/*425	36/*62	3075/*6300	6800/*13900	8.00TG	TL	24.0	30.2
A31G0039			13.00-24	12	A8/*A2	TL	G-2S	335	13.2	1275	50.2	40/*10	25/*5	300/*450	44/*65	2725/*5600	6000/*12300	8.00TG	TL	23.0	29.0
A31G0003	A3GG0047		13.00-24	14	A8/*A2	TL	G-2S	335	13.2	1275	50.2	40/*10	25/*5	350/*525	51/*76	3000/*6150	6600/*13600	8.00TG	TL	23.0	29.0
A31G0040			14.00-24	12	A8/*A2	TL	G-2S	360	14.2	1345	53.0	40/*10	25/*5	250/*425	36/*62	3075/*6300	6800/*13900	8.00TG	TL	24.0	30.2
A31G0005	A3GG0048		14.00-24	14	A8/*A2	TL	G-2S	360	14.2	1345	53.0	40/*10	25/*5	325/*500	47/*73	3450/*6800	7600/*15000	8.00TG	TL	24.0	30.2
	A3GG0009	A1AGO140	13.00-24	12	B/*A2	TL	E-3	350	13.8	1300	51.2	50/*10	30/*5	300/*450	44/*65	3000/*5600	6600/*12300	10.0	TL	28.0	35.3
		A1AGO176	13.00-24	18	B/*A2	TL	E-3	350	13.8	1300	51.2	50/*10	30/*5	450	65	3875	8550	10.0	TL	28.0	35.3
		A1AGO008	16.00-24	16	B/*A2	TT	E-3	425	16.7	1460	57.5	50/*10	30/*5	325/*425	47/*62	4875/*8250	10700/*18200	10.00VA	Z1-01-8	30.0	37.8
	A3GG0055	A1AGO010	16.00-24	16	B/*A2	TL	G-3/E-3	435	17.1	1460	57.5	50/*10	30/*5	325/*425	47/*62	4875/*8250	10700/*18200	10.00VA	TL	28.0	35.3
		11AGO027	16.00-24	16	B/*A2	TT	E-3B	425	16.7	1460	57.5	50/*10	30/*5	325/*425	47/*62	4875/*8250	10700/*18200	10.00VA	Z1-01-8	30.0	37.8
		11AGO028	16.00-24	20	B/*A2	TT	E-3B	425	16.7	1460	57.5	50/*10	30/*5	400/*550	58/*80	5450/*9750	12000/*21500	10.00VA	Z1-01-8	30.0	37.8
		11AGO007	13.00-24	12	A8/*A2	TT	G-2	340	13.4	1300	51.2	40/*10	25/*5	300/*450	44/*65	2725/*5600	6000/*12300	9.00VA	Z1-01-8	23.0	29.0
		11AGO008	13.00-24*	16	A8/*A2	TT	G-2	340	13.4	1300	51.2	40/*10	25/*5	400/*575	58/*83	3250/*6500	7150/*14300	9.00VA	Z1-01-8	23.0	29.0
A1TGO019		A1AGO194	14.00-24	12	A8/*A2	TL	G-2	360	14.2	1345	53.0	40/*10	25/*5	250/*425	36/*62	3075/*6300	6800/*13900	8.00TG	TL	30.0	37.8



BIAS OTR TYRES

BIAS OTR (GRADERS) TYRES

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max.Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
A3CG0001 ①	A3GG0001	A1AGO001	13.00-24	12	A8/*A2	TL	G-2A	335	13.2	1275	50.2	40/*10	25/*5	300/*450	44/*65	2725/*5600	6000/*12300	8.00TG	TL	23.0	29.0
	A3GG0054	11AGO098	13.00-24	14	A8/*A2	TL	G-2A	335	13.2	1275	50.2	40/*10	25/*5	350/*525	51/*76	3000/*6150	6600/*13600	8.00TG	TL	23.0	29.0
		A1AGO002	13.00-24	16	A8/*A2	TL	G-2A	335	13.2	1275	50.2	40/*10	25/*5	400/*575	58/*83	3250/*6500	7150/*14300	8.00TG	TL	23.0	29.0
		A1AGO149	13.00-24	18	A8/*A2	TL	G-2A	335	13.2	1275	50.2	40/*10	25/*5	450/*675	65/*98	3500/*7000	7700/*15450	8.00TG	TL	23.0	29.0
		A1AGO144	14.00-24*	10	A8/*A2	TL	G-2A	360	14.2	1345	53.0	40/*10	25/*5	225/*350	33/*51	2800/*5600	6150/*12300	8.00TG	TL	30.0	37.8
A1TG0001 ②	A3GG0002	A1AGO003	14.00-24	12	A8/*A2	TL	G-2A	360	14.2	1345	53.0	40/*10	25/*5	250/*425	36/*62	3075/*6300	6800/*13900	8.00TG	TL	30.0	37.8
		11AGO022	14.00-24	12	A8/*A2	TL	G-2A	360	14.2	1345	53.0	40/*10	25/*5	250/*425	36/*62	3075/*6300	6800/*13900	9.50	TL	30.0	37.8
A1TG0009 ③	A3GG0053	11AGO103	14.00-24	16	A8/*A2	TL	G-2A	360	14.2	1345	53.0	40/*10	25/*5	350/*550	51/*80	3650/*7300	8050/*16100	8.00TG	TL	30.0	37.8
		11AGO052	21.00-28*	24	A8	TT	G-2B	575	22.6	1790	70.5	40	25	350	51	9000	19800	15.00	Z1-01-10	25.0	31.5
	A3GG0018	A1AGO009	16.00-24	16	A8/*A2	TL	G-2C	435	17.1	1460	57.5	40/*10	25/*5	325/*425	47/*62	4500/*8250	9900/*18200	10.00VA	TL	28.0	35.3
		A1AGO137	13.00-24	12	A8/*A2	TL	G-2D	335	13.2	1275	50.2	40/*10	25/*5	300/*450	44/*65	2725/*5600	6000/*12300	8.00TG	TL	26.0	32.8
	A3GG0084	A1AGO138	14.00-24	12	A8/*A2	TL	G-2D	395	15.6	1360	53.5	40/*10	25/*5	36/*62	40/*62	3075/*6300	6800/*13900	8.00TG	TL	25.0	31.5

BIAS OTR (COMPACTOR) TYRES

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max.Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
		11AGE018	23.1-26	8	A2	TT	C-1A	595	23.4	1500	59.1	10	5	140	20	3950	8700	DW20	Z1-04-1	22.0	27.7
		11AGE013	23.1-26	12	A2	TT	C-1A	595	23.4	1500	59.1	10	5	200	29	5100	11250	DW20	Z1-04-1	22.0	27.7
		11AGE026	23.1-26*	14	A2	TT	C-1A	595	23.4	1500	59.1	10	5	230	33	5650	12450	DW20	Z1-04-1	22.0	27.7
		11AGE010	18.00-24	12	B/*A2	TT	C-3	495	19.5	1615	63.6	50/*10	30/*5	200/*275	29/*40	4750/*8250	10500/*18200	13.00	Z1-01-8	30.0	37.8
		11AGE011	18.00-24*	16	B/*A2	TT	C-3	495	19.5	1615	63.6	50/*10	30/*5	325/*375	47/*54	5600/*10000	12300/*22000	13.00	Z1-01-8	30.0	37.8
		11AGE012	18.00-24	20	B/*A2	TT	C-3	495	19.5	1615	63.6	50/*10	30/*5	350/*475	51/*69	6500/*11500	14300/*25400	13.00	Z1-01-8	30.0	37.8
		11AGE046	20.5-25	16	A6/*A2	TT	C-7	520	20.5	1490	58.7	10	5	350	51	8250	18150	17.00/2.0	DG09C	17.0	21.4
13SGE004 ④		11AGE019	23.1-26	8	A6/*A2	TT	C-7	595	23.4	1500	59.1	30/*10	20/*5	110/*140	16/*20	2825/*3950	6230/*8700	DW20	Z1-04-1	16.0	20.2
13SGE003 ⑤	13GGE001	11AGE014	23.1-26	12	A6/*A2	TT	C-7	595	23.4	1500	59.1	30/*10	20/*5	170/*200	25/*29	3655/*5100	8050/*11250	DW20	Z1-04-1	16.0	20.2
A2MGE005		11AGE016	23.1-26	14	A6/*A2	TT	C-7	595	23.4	1500	59.1	30/*10	20/*5	200/*230	29/*33	4050/*5650	8900/*12450	DW20	Z1-04-1	16.0	20.2
		11AGE020	23.1-26	16	A6/*A2	TT	C-7	595	23.4	1500	59.1	30/*10	20/*5	230/*260	33/*38	4395/*6150	9700/*13600	DW20	Z1-04-1	16.0	20.2
A1FGE002 ⑥		A1AGE002	23.1-26	8	A6/*A2	TL	C-7	595	23.4	1500	59.1	30/*10	20/*5	110/*140	16/*20	2825/*3950	6230/*8700	DW20	TL	16.0	20.2
A1FGE001 ⑦	A3GGE002	A1AGE001	23.1-26	12	A6/*A2	TL	C-7	595	23.4	1500	59.1	30/*10	20/*5	170/*200	25/*29	3655/*5100	8050/*11250	DW20	TL	16.0	20.2



BIAS OTR TYRES

BIAS OTR (COMPACTOR) TYRES

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max. Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
	I3GGE002	IIAGE015	23.1-26	12	A6/*A2	TL	C-7	595	23.4	1500	59.1	30/*10	20/*5	170/*200	25/*29	3655/*5100	8050/*11250	DW20	TL	16.0	20.2
		AIAGE003	23.1-26	14	A6/*A2	TL	C-7	595	23.4	1500	59.1	30/*10	20/*5	200/*230	29/*33	4050/*5650	8900/*12450	DW20	TL	16.0	20.2
		AIAGG011	23.1-26	14	A6/*A2	TL	C-7	595	23.4	1500	59.1	30/*10	20/*5	200/*230	29/*33	4050/*5650	8900/*12450	DW20	TL	16.0	20.2
		IIAGE017	23.1-26	16	A6/*A2	TL	C-7	595	23.4	1500	59.1	30/*10	20/*5	230/*260	33/*38	4395/*6150	9700/*13600	DW20	TL	16.0	20.2
		IIAGE023	23.1-26	8	A6/*A2	TT	C-7A	595	23.4	1500	59.1	30/*10	20/*5	110/*140	16/*20	2825/*3950	6230/*8700	DW20	Z1-04-1	16.0	20.2
		IIAGE024	23.1-26	12	A6/*A2	TT	C-7A	595	23.4	1500	59.1	30/*10	20/*5	170/*200	25/*29	3655/*5100	8050/*11250	DW20	Z1-04-1	16.0	20.2
	I3GGE003	IIAGE025	23.1-26	14	A6/*A2	TT	C-7A	595	23.4	1500	59.1	30/*10	20/*5	200/*230	29/*33	4050/*5650	8900/*12450	DW20	Z1-04-1	16.0	20.2
A1FGE004 ①		AIAGE007	23.1-26	8	A6/*A2	TL	C-7B	595	23.4	1500	59.1	30/*10	20/*5	110/*140	16/*20	2825/*3950	6230/*8700	DW20	TL	20.0	25.2
A1FGE003		AIAGE006	23.1-26	12	A6/*A2	TL	C-7B	595	23.4	1500	59.1	30/*10	20/*5	170/*200	25/*29	3655/*5100	8050/*11250	DW20	TL	20.0	25.2

BIAS FLOTATION OTR TYRES

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max. Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
A4GG0001		A1AGG034	18.00-25	12	A2	TL	E-7	510	20.1	1537	60.5	10	5	275	40	8250	18200	13.00	TL	15	18.9
A4GG0003		A1AGO196	18.00-25	16	A2	TL	E-7	510	20.1	1537	60.5	10	5	375	54	10000	22000	13.00	TL	15	18.9
A4GG0004			18.00-25	28	A2	TL	E-7	510	20.1	1537	60.5	10	5	650	94	13600	29920	13.00	TL	15	18.9
		A1AGO167	21.00-25	16	A2	TL	E-7	628	24.7	1654	65.1	10	5	325	47	11800	26000	15.00	TL	15	18.9
A4GG0002		A1AGO170	21.00-25	28	A2	TL	E-7	628	24.7	1654	65.1	10	5	575	83	16500	36400	15.00	TL	15	18.9
		A1AGD001	1500X600-435	18	C	TL	E-7A	600	23.5	1500	59.1	60	37.5	470	68	5750	12676	19.5/2.5	TL	18.0	22.7
		A1AGD002	1500*750-435	18	C	TL	E-7A	750	26.5	1500	59.1	60	37.5	470	68	6500	14330	19.5/2.5	TL	18.0	22.7
	A3GNN090	A1ANN134	550/60-22.5	16	A8	TL	I-3C	537	21.1	1254	49.4	40	25	300	44	*5300/**3750	*11670/**8260	16.00DC	TL	25.0	31.5
		A1ANN132	600/55-22.5	16	A8	TL	I-3C	600	23.6	1225	48.2	40	25	260	38	3450	7590	20.00	TL	26.0	32.8
A4GNN001			700/50-22.5	12	A8	TL	I-3C	700	27.6	1270	50.0	40	25	220	32	*5600/**4000	*12330/**8810	24.00DC	TL	27.0	34.0
A4GNN002			700/50-22.5	16	A8	TL	I-3C	700	27.6	1270	50.0	40	25	280	41	*6700/**4750	*14760/**10460	24.00DC	TL	27.0	34.0

NOTE: ① More PART.Nos are: I3SGE005

BIAS AGRICULTURAL TYRES

R-1 AGRI-TRAC

PART. No.	CAT. No.	ERP No.	Tyre Size	Ply Rating	Speed Symbol	Tyre Type	Pattern	Section Width		Overall Diameter		Max.Speed		Infl. Pressure		Max. Load		Design Rim Width	Tyre Valve	Tread Depth	
								mm	ins	mm	ins	km/h	mph	kPa	psi	kg	Lbs			(mm)	(32nds)
A31NN001			11.2-24	4	A6/*A8	TT	R-1K	285	11.2	1105	43.5	30/*40	20/*25	130/*120	19/*18	845/*750	1860/*1650	10.00	Z1-03-1	31.0	39.1
A31NP026			11.2-28	4	A6/*A8	TT	R-1K	285	11.2	1205	47.4	30/*40	20/*25	130/*120	19/*18	900/*800	1980/*1760	10.00	Z1-03-1	31.0	39.1
A31NN071			12.4-24	4	A6/*A8	TT	R-1K	315	12.4	1160	45.7	30/*40	20/*25	110/*110	16/*16	945/*850	2085/*1870	11.00	Z1-03-1	33.0	41.6
A31NN044			12.4-28	4	A6/*A8	TT	R-1K	315	12.4	1260	49.6	30/*40	20/*25	110/*110	16/*16	1005/*900	2215/*1980	11.00	Z1-03-1	33.0	41.6
A31NN117			12.4-28	8	A6	TT	R-1K	315	12.4	1260	49.6	30	20	230	33	1510	3330	11.00	Z1-03-1	33.0	41.6
A31NN063			14.9-24	6	A6/*A8	TT	R-1K	380	15.0	1265	49.8	30/*40	20/*25	140/*140	20/*20	1510/*1360	3330/*3000	13.00	Z1-03-1	36.0	45.4
A31NN088			14.9-24	6	A6/*A8	TT	R-1K	380	15.0	1265	49.8	30/*40	20/*25	140/*140	20/*20	1510/*1360	3330/*3000	13.00	Z1-03-1	36.0	45.4
A31NN084			14.9-24	8	A6/*A8	TT	R-1K	380	15.0	1265	49.8	30/*40	20/*25	180/*180	26/*26	1760/*1600	3880/*3520	13.00	Z1-03-1	36.0	45.4
A31NN089			14.9-24	8	A6/*A8	TT	R-1K	380	15.0	1265	49.8	30/*40	20/*25	180/*180	26/*26	1760/*1600	3880/*3520	13.00	Z1-03-1	36.0	45.4
A31NN003			12.4-24	4	A6/*A8	TT	R-1K	315	12.4	1160	45.7	30/*40	20/*25	110/*110	16/*16	945/*850	2085/*1870	11.00	Z1-03-1	36.0	45.4
A31NN005			13.6-28	6	A6/*A8	TT	R-1K	345	13.6	1310	51.6	30/*40	20/*25	160/*150	23/*22	1430/*1285	3155/*2830	12.00	Z1-03-1	37.0	46.6
A31NN083			13.6-28	8	A6/*A8	TT	R-1K	345	13.6	1310	51.6	30/*40	20/*25	210/*190	30/*28	1645/*1500	3640/*3300	12.00	Z1-03-1	37.0	46.6
A31NN006			13.6-38	8	A6	TT	R-1K	345	13.6	1565	61.6	30	20	200	29	1910	4210	12.00	Z1-03-1	37.0	46.6
A31NN076			13.6-38	10	A6	TT	R-1K	345	13.6	1565	61.6	30	20	250	36	2215	4885	12.00	Z1-03-1	37.0	46.6
A31NN008			14.9-24	6	A6/*A8	TT	R-1K	380	15.0	1265	49.8	30/*40	20/*25	140/*140	20/*20	1510/*1360	3330/*3000	13.00	Z1-03-1	38.0	47.9
A31NN009			14.9-28	6	A6/*A8	TT	R-1K	380	15.0	1365	53.7	30/*40	20/*25	140/*140	20/*20	1610/*1450	3550/*3200	13.00	Z1-03-1	38.0	47.9
A31NN085			14.9-28	8	A6/*A8	TT	R-1K	380	15.0	1365	53.7	30/*40	20/*25	180/*180	26/*26	1880/*1700	4145/*3740	13.00	Z1-03-1	38.0	47.9
A31NN010			15.5-38	8	A6	TT	R-1K	395	15.6	1570	61.8	30	20	180	26	2060	4540	14.00	Z1-03-1	37.0	46.6
A31NN077			15.5-38	8	A6	TT	R-1K	395	15.6	1570	61.8	30	20	230	33	2320	5115	14.00	Z1-03-1	37.0	46.6
A31NN014			16.9-24	8	A6/*A8	TT	R-1K	430	16.9	1335	52.6	30/*40	20/*25	170/*170	24/*24	2040/*1850	4500/*4080	15.00	Z1-03-1	39.6	49.9
A31NN015			16.9-28	6	A6/*A8	TT	R-1K	430	16.9	1435	56.5	30/*40	20/*25	130/*120	19/*18	1840/*1650	4055/*3640	15.00	Z1-03-1	39.0	49.1
A31NN074			16.9-28	8	A6/*A8	TT	R-1K	430	16.9	1435	56.5	30/*40	20/*25	170/*170	24/*24	2175/*1950	4795/*4300	15.00	Z1-03-1	39.0	49.1
A31NN016			16.9-30	6	A6/*A8	TT	R-1K	430	16.9	1485	58.5	30/*40	20/*25	130/*120	19/*18	1900/*1700	4190/*3740	15.00	Z1-03-1	39.0	49.1
A31NN073			16.9-30	8	A6/*A8	TT	R-1K	430	16.9	1485	58.5	30/*40	20/*25	170/*170	24/*24	2245/*2000	4950/*4400	15.00	Z1-03-1	39.0	49.1
A31NN090			16.9-30	14	A6	TT	R-1K	430	16.9	1485	58.5	30	20	270	39	2950	6500	15.00	Z1-03-1	39.0	49.1
A31NN017			16.9-34	6	A6/*A8	TT	R-1K	430	16.9	1585	62.4	30/*40	20/*25	130/*120	19/*18	2015/*1800	4440/*3960	15.00	Z1-03-1	39.0	49.1
A31NN018			16.9-38	8	A6/*A8	TT	R-1K	430	16.9	1685	66.3	30/*40	20/*25	170/*170	24/*24	2520/*2240	5555/*4940	15.00	Z1-03-1	39.0	49.1
A31NN094			16.9-38	8	A6/*A8	TT	R-1K	430	16.9	1685	66.3	30/*40	20/*25	170/*170	24/*24	2520/*2240	5555/*4940	15.00	Z1-03-1	39.0	49.1
A31NN078			16.9-38	10	A6	TT	R-1K	430	16.9	1685	66.3	30	20	200	29	2760	6085	15.00	Z1-03-1	39.0	49.1
A31NN093			16.9-38	10	A6	TT	R-1K	430	16.9	1685	66.3	30	20	200	29	2760	6085	15.00	Z1-03-1	39.0	49.1
A31NN022			18.4-26	6	A6/*A8	TT	R-1K	465	18.3	1450	57.1	30/*40	20/*25	110/*110	16/*16	1990/*1800	4385/*3960	16.00	Z1-03-1	39.6	49.9
A31NN023			18.4-30	6	A6/*A8	TT	R-1K	465	18.3	1550	61.0	30/*40	20/*25	110/*110	16/*16	2120/*1900	4675/*4190	16.00	Z1-03-1	39.6	49.9
A31NN086			18.4-30	8	A6/*A8	TT	R-1K	465	18.3	1550	61.0	30/*40	20/*25	140/*140	20/*20	2415/*2180	5325/*4800	16.00	Z1-03-1	39.6	49.9
A31NN045			18.4-30	10	A6/*A8	TT	R-1K	465	18.3	1550	61.0	30/*40	20/*25	180/*180	26/*26	2815/*2500	6205/*5520	16.00	Z1-03-1	39.6	49.9
A31NN024	A3GNN070		18.4-34	8	A6/*A8	TT	R-1K	465	18.3	1655	65.2	30/*40	20/*25	140/*140	20/*20	2565/*2300	5655/*5080	16.00	Z1-03-1	39.6	49.9
A31NN046			18.4-34	10	A6	TT	R-1K	465	18.3	1655	65.2	30	20	180	26	2990	6590	16.00	Z1-03-1	39.6	49.9
A31NN025	A3GNN071		18.4-38	8	A6/*A8	TT	R-1K	465	18.3	1755	69.1	30/*40	20/*25	140/*140	20/*20	2715/*2430	5985/*5360	16.00	Z1-03-1	39.6	49.9
A31NN047			18.4-38	10	A6/*A8	TT	R-1K	465	18.3	1755	69.1	30/*40	20/*25	180/*180	26/*26	3165/*2900	6975/*6400	16.00	Z1-03-1	39.6	49.9
A31NN079			18.4-38	12	A6/*A8	TT	R-1K	465	18.3	1755	69.1	30/*40	20/*25	230/*220	33/*32	3575/*3250	7880/*7150	16.00	Z1-03-1	39.6	49.9
A31NN027			20.8-38	8	A6/*A8	TT	R-1K	530	20.9	1835	72.2	30/*40	20/*25	130/*120	19/*18	3090/*2800	6810/*6150	18.00	Z1-03-1	42.0	52.9
A31NN075			20.8-38	10	A6/*A8	TT	R-1K	530	20.9	1835	72.2	30/*40	20/*25	160/*150	23/*22	3475/*3150	7660/*6950	18.00	Z1-03-1	42.0	52.9
A31NN092		A1ANN034	20.8-38	12	A6/*A8	TT	R-1K	530	20.9	1835	72.2	30/*40	20/*25	200/*190	29/*28	4000/*3550	8800/*7850	18.00	Z1-03-1	42.0	52.9
A31NN091			20.8-38	14	A8	TT	R-1K	530	20.9	1835	72.2	40	25	220	32	3875	8550	18.00	Z1-03-1	42.0	52.9
A31NN030			23.1-26	10	A6/*A8	TT	R-1K	590	23.2	1605	63.2	30/*40	20/*25	140/*140	20/*20	3245/*2900	7155/*6400	20.00	Z1-03-1	42.0	52.9
		I1ANN089	23.1-26	12	A6/*A8	TT	R-1K	590	23.2	1605	63.2	30/*40	20/*25	170/*170	24/*24	3610/*3250	7960/*7150	20.00	Z1-03-1	42.0	52.9
A31NN080			23.1-26	14	A6/*A8	TT	R-1K	590	23.2	1605	63.2	30/*40	20/*25	200/*190	29/*28	3970/*3550	8750/*7850	20.00	Z1-03-1	42.0	52.9
A31NN031			24.5-32	10	A6/*A8	TT	R-1K	625	24.6	1805	71.1	30/*40	20/*25	140/*140	20/*20	3950/*3550	8710/*7850	21.00	Z1-03-1	43.0	54.2
A31NN087			24.5-32	12	A6/*A8	TT	R-1K	625	24.6	1805	71.1	30/*40	20/*25	170/*170	24/*24	4390/*4000	9680/*8800	21.00	Z1-03-1	43.0	54.2